

LME8108M1AL1MA506

8CH 5.0MP 5 IN 1 XVR KIT



| | |
|-------------------|--|
| Model | LME8108M1AL1MA506 |
| 5 IN 1 XVR | |
| Operating System | Embedded LINUX |
| Video | |
| Encoding Format | H.265 |
| Monitor Quality | VGA, HDMI |
| Preview Ability | 8*5M-N |
| Encode Ability | 8*5M-N (5 in 1) |
| Decode Ability | 8*5M-N (5 in 1) |
| Multi-mode Input | Analog: 8*5M-N; 8*4M-N; 4*1080P; Hybrid: 8*1080N(analog)+8*1080P(network); Network: 16*1080P;8*5M |
| Motion Detection | Each screen can be set to 192 (16*12) detection areas; Multi-level sensitivity can be set (Limited local channel) |
| Audio | |

| | | |
|------------------------------|--|--------------------------|
| Audio Compression | G.711A | |
| Intercom | Support | |
| Record & Playback | | |
| Record Mode | Manual>Alarm>Motion detection>Timing | |
| Local Playback | 8CH (analog input mode) | |
| Search Mode | Search by time, calendar, event, channel | |
| Storage & backup | | |
| Video Storage | HDD, Network | |
| Backup Mode | Network, USB hard disk, USB burner, SATA burner | |
| External Interface | | |
| Video Input | 8CH BNC | |
| Video Output | 1CH VGA, 1ch HDMI | |
| Audio I/O | 4/1 | |
| Network Interface | RJ45 10M/100M self-adaption | |
| PTZ Control | Support kinds of PTZ protocols | |
| USB | 2* USB ports | |
| HDD | 1*SATA ports (Max 8TB/per) | |
| General | | |
| Power Supply | 12V/2A | |
| Power Consumption | <15W (without HDD) | |
| Working Environment | Temperature:0°C— +55°C, Humidity:10%—90%, Atm:86kpa—106kpa | |
| Camera | Metal Dome*4PCS | Metal Bullet*4PCS |
| Image Sensor | 1/2.7" CMOS Image Sensor | |
| Resolution | 5MP | |
| Effective Pixels | 2560(H) × 1920(V) | |
| Resolution | AHD | |
| Video Standard | PAL/NTSC | |
| Synchronization | Inter-Sync | |
| IR Distance | 20-25m | 30-35m |
| Lens | 3.6mm/5.0MP | |
| Day & Night mode | External control | |
| Min. Illumination | 0.01Lux/F1.2 | |
| UTC | Support | |

| | | |
|---|------------------------------------|-----------------------------|
| OSD | Support | |
| WDR | Digital WDR | |
| S/N Ratio | ≥55dB | |
| Electronic Shutter | AUTO 1/50(60)~1/50000s | |
| White Balance | Auto | |
| AGC | Auto | |
| Video Output | AHD | |
| Dynamic Range | 68db | |
| DNR | 3D DNR | |
| Type | Metal Dome Camera | Outdoor Metal Bullet Camera |
| Video Port | BNC | |
| Power Supply | 12 V DC±10% | |
| Lightning protection | Support | |
| Power Consumption | Max 5W | |
| Working Humidity | Relative humidity less than 90% | |
| Operating Temp | -20°C to +50°C (- 14°F to 122°F) | |
| Storage Temp. | -40°C to +60°C (-40°F to 140°F) | |
| Package | | |
| 8CH 5 IN 1 XVR (Mouse ,12V 2A Power Adaptor) *1PC | | |
| 5.0MP IR Metal Bullet Camera * 4PCS | | |
| 5.0MP IR Metal Dome Camera * 4PCS | | |
| 15M BNC & Power Cable * 8PCS | | |
| 1 Split to 4 Power Line * 2PCS | | |
| 12V 2A Power Adaptor for Camera * 2PCS | | |