

## MAVR104D-H3

4CH 1080P AHD Dual-SD Mobile DVR(Wifi,GPS,4G)



Model Number	MAVR104D-H3
<b>System</b>	
Master	HI3520DV300(A7@600MHZ)
RAM	Samsung 1*4G DDR
OS	Linux
GUI	Graphic OSD
Video Compression	H.264
Video Standard	PAL/NTSC(Default)
USER	The average user (000000) /Administrator level management (111111)
<b>Video &amp; Audio</b>	
Preview	1080P/960P/D1/CIF
Digital	4*1080P/4*960P/2*960+2*D1/4*D1
Image quality	1-8 levels adjustable (1 is the best)
Decode ability	4 CH 1080P(15fps)
Compression	G726
Video Input	1.0Vp-p, 75Ω
Video Input	1CH CVBS output + VGA output, 1.0Vp-p, 75Ω
Audio Input	3Vp-p, 1KΩ
Audio output	1CH ,2Vp-p 600Ω
<b>Storage &amp; Playback</b>	
Record mode	manual>alarm>timing
Storage	Two SD Card (max256G)

Video search	Search by time, calendar, event, channel
Backup mode	USB burner
<b>Hardware Port</b>	
Audio video input	Four minutes of aviation connector car line,4 core joint (1=12V 2=GND 3=Audio 4=Video)
Audio video output	1CH VGA, 1 way aerial head audio and video output
IO	4 way alarm trigger input (High/low level)
	2 way alarm high level output (12V)
	1PC DC12V Output
	1CH RS232 OR 1CH RS485
SD Card	2PCS SD Card Port (max 256G)
USB	1* USB 2.0 ports
Power	1PCS (Support 8-36V DC voltage input)
Electronic lock	1PC
LED lights	PWR/ARW/SD1/SD2/GPS/NET
<b>Network</b>	
RJ45	1pcs RJ45 Port
GPS	support
Wifi	support
4G/3G	All Netcom
APP	Support Android,IOS
PC	support
<b>Function</b>	
Low voltage protection	Shutdown when the adjustable voltage of the equipment is too low
Communication protocol	Support multiple IP upload multiple servers at the same time
File encryption	Support encrypted channels
Power-off protection	The sudden power failure of the equipment serves to protect files
Back gauge	Can set the reverse ruler display switch
<b>Other</b>	
Output voltage	12V/4A
Temperature	-20°C--70°C
Storage situation	1CH 960P (about 800M/H) 1CH 1080P(about 1.5G/H)
The net weight	About 500g
Size	142MM *145MM *49MM
Power Consumption	Max 18W