mapesen[®]

MP-B406I216M-WTA2

Smart Wifi SD Card 4 Inch Speed Dome Camera





Model	MP-B406I216M-WTA2
Camera	
Image Sensor	1/2.8" SONY color CMOS
Effective Pixels	2.0MP/1080P
Synchronization	Internal
Code Format	H265/H264
Code Rate	32Kbps~6144Kbps adjustable, default 1536kbps
Stream	Dual-stream
Frame Rate	Main code stream:1080P@25fps/30fps
	Auxiliary stream: D1/640x352@ 25/30fps

Smart WIFI SD Card Series | MP-B406I216M-WTA2



Min. Illumination	0.01LUX/F1.2 color,0.005LUX/F1.2 WITH IR ON (BW)
Day & Night Mode	Color/B&W/Intelligent model
Electronic Shutter	Auto
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	3D DNR
SNR	≥48dB
IR board	8PCS IR Array LEDs
IR Distance	100m
PTZ	
Horizontal Angle	0-355°
Vertical Angle	0-90°
Pan Speed	1°-40°/S
Tilt Speed	1°-20°/S
Preset Point	8 preset points
cruise	1 x AB line scan
Functions	
Motion Detection	Support
Snapshot	Support
Email Alarm	Support
Alarm linkage	The mobile detection alarm is pushed to the APP
Mirror Image	Flip horizontal/vertical
Audio	Two-way audio, built-in microphone and outside speaker
Storage	Built-in Micro SD card slot, Max128G, timer capture
Web Access	Support IE, Google, Firefox browser, Built-in webserver to facilitate the user to use the standard IE browser to achieve the front end of the real-time browsing and setting management
Lens	
Focal Length	4.7-86.4mm
Optical Zoom	20X
Lens Megapixel	3 Megapixel fixed lens
NETWORK	
Network Interface	1*RJ45 10M/100M Ethernet Port
WIFI	WIFI 802.11b/g/n
AP	Support
P2P	Support Max 6users, browsing at the same time (each stream: 3 users)
Mobile Surveillance	iOS, Android
PC	Support

Smart WIFI SD Card Series | MP-B406I216M-WTA2



Interface		
Antenna	1 * WIFI	
Storage	1PC Micro SD card	
Reset	Support key reset	
Ethernet	1PC RJ45	
General		
Working Temperature	-30 °C to +60 °C	
Working Humidity	10%-90% RH (Non-condensing)	
Power Supply	DC12V2A	
Lightning protection	GB/T17626.5, IEC61000-4-5	
Power Consumption	Max 10W	
Housing	Outdoor Metal Bullet	
Weather Proof	IP67	
Size	154x137x239mm	