MP-B406I500M-WTA2

Smart Wifi SD Card 4 Inch Speed Dome Camera

Model	MP-B306I500M-WTA2
Camera	
Image Sensor	1/2.8" SONY color CMOS
Effective Pixels	5.0MP
Synchronization	Internal
Code Format	H265/H264
Code Rate	32Kbps~6144Kbps adjustable, default 1536kbps
Stream	Dual-stream
Frame Rate	Main code stream: 5MP(2560x1920)@20fp,4MP(2560x1440)@20fps
	Auxiliary stream: 800x448@20fps,640x352@20fps

Min. Illumination	0.1LUX/F1.2 color,0.01LUX/F1.2 WITH IR ON (BW)
Day & Night Mode	Color/B&W/Intelligent model
Electronic Shutter	Auto
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	3D DNR
SNR	≥48dB
IR board	8PCS IR Array LEDs
IR Distance	100m
PTZ	
Horizontal Angle	0-355°
Vertical Angle	0-90°
Pan Speed	0.1°-40°/S
Tilt Speed	0.1°-20°/S
Preset Point	8 preset points
cruise	1 x AB line scan
Functions	
Motion Detection	Support
Snapshot	Support
Email Alarm	Support
Alarm linkage	The mobile detection alarm is pushed to the APP
Mirror Image	Flip horizontal/vertical
Voice intercom	Built-in microphone and outside speaker
Storage	Built-in Micro SD card slot, Max128G, timer capture
Web Access	Support IE, Google, Firefox browser, Built-in webserver to facilitate the user to use the standard IE browser to achieve the front end of the real-time browsing and setting management
Lens	
Focal Length	4.7-86.4mm
Optical Zoom	20X
Lens Megapixel	3 Megapixel fixed lens
NETWORK	
Network Interface	1*RJ45 10M/100M Ethernet Port
WIFI	WIFI 802.11b/g/n
AP	Support
P2P	Support Max 6users, browsing at the same time (each stream: 3 users)
Mobile Surveillance	iOS, Android
PC	Support

Interface	
Antenna	1 * WIFI
Storage	1PC Micro SD card
Reset	Support key reset
Ethernet	1PC RJ45
General	
Working Temperature	-30 °C to +60 °C
Working Humidity	10%-90% RH (Non-condensing)
Power Supply	DC12V2A
Lightning protection	GB/T17626.5, IEC61000-4-5
Power Consumption	Max 10W
Housing	Outdoor Metal Bullet
Weather Proof	IP67
Size	154x137x239mm