

MP-F5BI500F

5.0MP Network Vandalproof Dome Camera



| | |
|-----------------------|--|
| Model Number | MP-F5BI500F |
| Camera | |
| Image Sensor | 1/2.8" SONY color CMOS |
| Min. Illumination | Color: 0.01Lux @F1.2, B/W: 0Lux with IR on |
| Lens | 3.6mm |
| Shutter Time | Auto |
| IR Distance | 20-25m |
| IR Board | 12pcs SMT LEDs |
| White Balance | Auto / Manual |
| AGC | Auto |
| WDR | Digital WDR |
| DNR | 2D/3D DNR |
| BLC | support |
| HLC | support |
| Video | |
| Max. Image Resolution | 5MP(2592*1944)@15fps |
| Frame Rate | Main code stream: 5MP@15fps,4MP/3MP@25fps,1080P/720P@30fps Auxiliary stream: D1/VGA/640x352/CIF@25fps |
| Video Compression | H265+/H265/H264 |
| Video Bit Rate | 500Kbps-6000Kbps support self-adjustable as needed |
| Image Settings | Brightness,Contrast,Saturation,Exposure,Upside Down,Mirror Adjustable |

| | |
|----------------------|---|
| Bit Superposition | Support OSD name,time and date information superposition |
| Web Access | Internet explorer 6.0 and above (Web Server embedded in device) browser |
| Audio | |
| Audio I/O | No |
| Audio compression | G.711 |
| Network | |
| Network Interface | 1*RJ45 10M/100M Ethernet Port |
| Networking Protocol | TCP/IP, HTTP, RTSP, DHCP, NTP, UPNP |
| ONVIF | ONVIF2.6 |
| APP | Support android, IOS |
| PC | Support |
| System | |
| Alarm I/O | Motion detection alarm |
| Storage | No |
| Motion Detection | 22*18 windows motion detection areas can be setting (sensitivity setting 1-100) |
| Video Mask | Support |
| Action with Alarm | Push to mobile APP |
| General | |
| Language Support | CHN(S)/CHN(T)/ENG |
| Power Supply | DC12V±10% |
| Power Consumption | Max 5W |
| Lightning protection | 2KV |
| Housing | Vandalproof Dome |
| Weather Proof | IP67 |
| Working Temperature | -30 °C to 85 °C |
| Working Humidity | 10%-95% (Non-condensing) |