

# MP-F5DI801F-PTA3

8.0MP/4K POE Network Vandalproof Dome Camera with Alarm, Audio, TF CARD Storage



|                       |   |
|-----------------------|---|
| <b>Model Number</b>   | <b>MP-F5DI801F-PTA3</b>   |
| <b>Camera</b>         |   |
| Image Sensor          | 1/2.5" color SONY CMOS  |
| Min. Illumination     | Color: 0.01Lux @F1.2, B/W: 0.001Lux with IR on  |
| Lens                  | 4.5mm   |
| Shutter Time          | Auto  |
| IR Distance           | 25-30m  |
| IR Board              | 18pcs SMT LEDs  |
| White Balance         | Auto / Manual   |
| AGC                   | Auto  |
| WDR                   | Super Digital WDR   |
| DNR                   | 2D/3D DNR   |
| BLC                   | support   |
| HLC                   | support   |
| Defog                 | support   |
| <b>Video</b>          |   |
| Max. Image Resolution | 8MP(3840x2160)  |
| Frame Rate            | Main code stream:3840*2160/1080P@25/30fpsfps;<br>Sub Stream :704x576;352*288@25/30fps |

|                      |   |
|----------------------|---|
| Video Compression    | H.265/H.264   |
| Video Bit Rate       | 160Kbps-20Mbps support self-adjustable as needed,default 8M;                    |
| Image Settings       | Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable      |
| Bit Superposition    | Support OSD name, time and date information superposition                       |
| Web Access           | Internet explorer 6.0 and above (Web Server embedded in device) browser         |
| <b>Audio</b>         |   |
| Audio I/O            | 1 Audio Input,1 Audio output interface  |
| Audio compression    | G.711a  |
| <b>Network</b>       |   |
| Network Interface    | 1*RJ45 10M/100M Ethernet Port   |
| Networking Protocol  | TCP/IP, UDP, HTTP, IGMP,ICMP, DNS,DDNS,FTP,SMTP, SNMP,RTP,RTSP, DHCP, NTP, UPNP |
| ONVIF                | ONVIF2.6  |
| APP                  | Support android, IOS  |
| PC                   | Support   |
| <b>System</b>        |   |
| Alarm I/O            | 1ch Alarm I/O,and Motion detection alarm  |
| Storage              | Support Max 128 TF/SD Card Storage  |
| Advanced Function    | Support WEB Configuration OSD,Motion detection,corridor model,etc               |
| SIP/VoIP Support     | Yes,Voice&Video-over-IP   |
| Event Trigger        | Motion detection,network disconnection,Video masking,etc                        |
| Event Action         | After the motion detection alarm center remind,the screen pops up linkage       |
| Safety Properties    | Support password protection,watermark function                                  |
| System Compatibility | ONVIF   |
| <b>General</b>       |   |
| POE                  | IEEE802.3af   |
| Power Supply         | DC12V±10% / POE   |
| Power Consumption    | Max 6W  |
| Lightning protection | Support   |
| Housing              | Vandalproof Dome  |
| Weather Proof        | IP66  |
| Working Temperature  | -30 °C to 85 °C   |
| Working Humidity     | 10%-95% (Non-condensing)  |