

# THM8104L1ML1MA506

4CH 5.0MP 5 IN 1 XVR KIT



<b>Model</b>	<b>THM8104L1ML1MA506</b>
<b>5 IN 1 XVR</b>	
Operating System	Embedded LINUX
<b>Video</b>	
Encoding Format	H.265
Monitor Quality	VGA, HDMI
Preview Ability	4*5M-N
Encode Ability	4*5M-N (5 in 1)
Decode Ability	4*5M-N (5 in 1)
Multi-mode Input	Analog: 4*5M-N; 4*4M-N; 4*1080P Hybrid: 2*1080P(analog) + 2*1080P(network) Network: 16*1080P; 4*5M
Motion Detection	Each screen can be set to 192 (16*12) detection areas; Multi-level sensitivity can be set (Limited local channel)
<b>Audio</b>	
Audio Compression	G.711A
Intercom	Support

Record & Playback	
Record Mode	Manual>Alarm>Motion detection>Timing
Local Playback	4CH (analog input mode)
Search Mode	Search by time, calendar, event, channel
Storage & backup	
Video Storage	HDD, Network
Backup Mode	Network, USB hard disk, USB burner, SATA burner
External Interface	
Video Input	4CH BNC
Video Output	1CH VGA, 1ch HDMI
Audio I/O	1/1
Network Interface	RJ45 10M/100M self-adaption
PTZ Control	Support kinds of PTZ protocols
USB	2* USB ports
HDD	1*SATA ports (Max 8TB/per)
General	
Power Supply	12V/2A
Power Consumption	<15W (without HDD)
Working Environment	Temperature:0°C— +55°C, Humidity:10%—90%, Atm:86kpa—106kpa
Camera	Metal Bullet*4PCS
Image Sensor	1/2.7" CMOS Image Sensor
Resolution	5MP
Effective Pixels	2560(H) × 1920(V)
Resolution	AHD
Video Standard	PAL/NTSC
Synchronization	Inter-Sync
IR Distance	20-25m
Lens	3.6mm/5.0MP
Day & Night mode	External control
Min. Illumination	0.01Lux/F1.2
UTC	Support
OSD	Support
WDR	Digital WDR

S/N Ratio	≥55dB
Electronic Shutter	AUTO 1/50(60)~1/50000s
White Balance	Auto
AGC	Auto
Video Output	AHD
Dynamic Range	68db
DNR	3D DNR
Type	Outdoor Metal Bullet Camera
Video Port	BNC
Power Supply	12 V DC±10%
Lightning protection	Support
Power Consumption	Max 5W
Working Humidity	Relative humidity less than 90%
Operating Temp	-20°C to +50°C ( - 14°F to 122°F )
Storage Temp.	-40°C to +60°C ( -40°F to 140°F )

<b>Package</b>	
4CH 5 IN 1 XVR ( Mouse,12V 2A Power Adaptor ) *1PC	
5.0MP IR Metal Bullet Camera * 4PCS	
15M BNC & Power Cable * 4PCS	
1 Split to 4 Power Line * 1PC	
12V 2A Power Adaptor for Camera * 1PC	