

TLM5104L1ML1MA206

4CH 2.0MP 5 IN 1 XVR KIT



| | |
|-------------------|--|
| Model | TLM5104L1ML1MA206 |
| 5 IN 1 XVR | |
| Operating System | Embedded LINUX |
| Video | |
| Encoding Format | H.264 |
| Monitor Quality | VGA, HDMI |
| Preview Ability | 4*1080N |
| Encode Ability | 4*1080N (5 in 1) |
| Decode Ability | 4*1080N (5 in 1) |
| Multi-mode Input | Analog: 4*1080N; 4*720P; 4*960H Hybrid: 2*720P(Coaxial)+ 2*720P(Network) Network: 8*1080P; 12*960P; 8*720P; 4*1080P; 4*720P; 1*1080P |
| Motion Detection | Each screen can be set to 192 (16 * 12) detection areas; Multi-level sensitivity can be set (Limited local channel) |
| Audio | |
| Audio Compression | G.711A |
| Intercom | Support |

| Record & Playback | |
|---------------------|--|
| Record Mode | Manual>Alarm>Motion detection>Timing |
| Local Playback | 4CH (analog input mode) |
| Search Mode | Search by time, calendar, event, channel |
| Storage & backup | |
| Video Storage | HDD, Network |
| Backup Mode | Network, USB hard disk, USB burner, SATA burner |
| External Interface | |
| Video Input | 4CH BNC |
| Video Output | 1CH VGA, 1ch HDMI |
| Audio I/O | 1/1 |
| Network Interface | RJ45 10M/100M self-adaption |
| PTZ Control | Support kinds of PTZ protocols |
| USB | 2* USB ports |
| HDD | 1*SATA ports (Max 8TB/per) |
| General | |
| Power Supply | 12V/2A |
| Power Consumption | <15W (without HDD) |
| Working Environment | Temperature:0°C— +55°C, Humidity:10%—90%, Atm:86kpa—106kpa |
| Camera | Metal Bullet*4PCS |
| Image Sensor | 1/2.7" CMOS Image Sensor |
| Resolution | 1080P@25/30fps |
| Effective Pixels | 1920(H) × 1080(V) |
| Resolution | AHD |
| Video Standard | PAL/NTSC |
| Synchronization | Inter-Sync |
| IR Distance | 30-35m |
| Lens | 3.6mm/2.0MP |
| Day & Night mode | External control |
| Min. Illumination | 0.01Lux/F1.2 |
| UTC | Support |
| OSD | Support |
| WDR | Digital WDR |

| | |
|--|------------------------------------|
| S/N Ratio | ≥58dB |
| Electronic Shutter | AUTO 1/50(60)~1/50000s |
| White Balance | Auto |
| AGC | Auto |
| Video Output | AHD |
| Dynamic Range | 60db |
| DNR | 2D DNR |
| Type | Outdoor Metal Bullet Camera |
| Video Port | BNC |
| Power Supply | 12 V DC±10% |
| Lightning protection | Support |
| Power Consumption | Max 4W |
| Working Humidity | Relative humidity less than 90% |
| Operating Temp | -20°C to +50°C (- 14°F to 122°F) |
| Storage Temp. | -40°C to +60°C (-40°F to 140°F) |
| Package | |
| 4CH 5 IN 1 XVR (Mouse,12V 2A Power Adaptor) *1PC | |
| 2.0MP IR Metal Bullet Camera * 4PCS | |
| 15M BNC & Power Cable * 4PCS | |
| 1 Split to 4 Power Line * 1PC | |
| 12V 2A Power Adaptor for Camera * 1PC | |