

# TLM5104P1AP1AA206

4CH 2.0MP 5 IN 1 XVR KIT



<b>Model</b>	TLM5104P1AP1AA206
<b>5 IN 1 XVR</b>	
Operating System	Embedded LINUX
<b>Video</b>	
Encoding Format	H.264
Monitor Quality	VGA, HDMI
Preview Ability	4*1080N
Encode Ability	4*1080N (5 in 1)
Decode Ability	4*1080N (5 in 1)
Multi-mode Input	Analog: 4*1080N; 4*720P; 4*960H Hybrid: 2*720P(Coaxial)+ 2*720P(Network) Network: 8*1080P; 12*960P; 8*720P; 4*1080P; 4*720P; 1*1080P
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; Multi-level sensitivity can be set (Limited local channel)
<b>Audio</b>	
Audio Compression	G.711A
Intercom	Support

Record & Playback	
Record Mode	Manual>Alarm>Motion detection>Timing
Local Playback	4CH (analog input mode)
Search Mode	Search by time, calendar, event, channel
Storage & backup	
Video Storage	HDD, Network
Backup Mode	Network, USB hard disk, USB burner, SATA burner
External Interface	
Video Input	4CH BNC
Video Output	1CH VGA, 1ch HDMI
Audio I/O	1/1
Network Interface	RJ45 10M/100M self-adaption
PTZ Control	Support kinds of PTZ protocols
USB	2* USB ports
HDD	1*SATA ports (Max 8TB/per)
General	
Power Supply	12V/2A
Power Consumption	<15W (without HDD)
Working Environment	Temperature:0°C— +55°C, Humidity:10%—90%, Atm:86kpa—106kpa
Camera	
	<b>Plastic Bullet*4PCS</b>
Image Sensor	1/2.7" CMOS Image Sensor
Resolution	1080P@25/30fps
Effective Pixels	1920(H) × 1080(V)
Resolution	AHD
Video Standard	PAL/NTSC
Synchronization	Inter-Sync
IR Distance	25-30m
Lens	3.6mm/2.0MP
Day & Night mode	External control
Min. Illumination	0.01Lux/F1.2
UTC	Support
OSD Support	Support
WDR	Digital WDR

S/N Ratio	≥58dB
Electronic Shutter	AUTO 1/50(60)~1/50000s
White Balance	Auto
AGC	Default
Video Output	AHD
Dynamic Range	60db
DNR	2D DNR
Type	Indoor Plastic Bullet Camera
Video Port	BNC
Power Supply	12 V DC±10%
Lightning protection	Support
Power Consumption	Max 4W
Working Humidity	Relative humidity less than 90%
Operating Temp	-20°C to +50°C ( - 14°F to 122°F )
Storage Temp.	-40°C to +60°C ( -40°F to 140°F )

<b>Package</b>	
4CH 5 IN 1 XVR ( Mouse,12V 2A Power Adaptor ) *1PC	
2.0MP IR Plastic Bullet Camera * 4PCS	
15M BNC & Power Cable * 4PCS	
1 Split to 4 Power Line * 1PC	
12V 2A Power Adaptor for Camera * 1PC	