

# TLM5108L1ML1MA206

8CH 2.0MP 5 IN 1 XVR KIT



|                   |   |
|-------------------|---|
| <b>Model</b>      | <b>TLM5108L1ML1MA206</b>  |
| <b>5 IN 1 XVR</b> |   |
| Operating System  | Embedded LINUX  |
| <b>Video</b>      |   |
| Encoding Format   | H.264   |
| Monitor Quality   | VGA, HDMI   |
| Preview Ability   | 8*1080N   |
| Encode Ability    | 8*1080N (5 in 1)  |
| Decode Ability    | 8*1080N (5 in 1)  |
| Multi-mode Input  | Analog: 8*1080N; 4*1080P;8*720P; 8*960H<br>Hybrid: 2*1080P(analog)+ 2*1080P(network);<br>4*1080N(analog)+4*960P(analog);<br>Network: 16*1080P;9*1080P; 16*960P;4*5M |
| Motion Detection  | Each screen can be set to 192 (16 * 12) detection areas;<br>Multi-level sensitivity can be set (Limited local channel)  |

| <b>Audio</b>                 |   |
|------------------------------|---|
| Audio Compression            | G.711A  |
| Intercom                     | Support   |
| <b>Record &amp; Playback</b> |   |
| Record Mode                  | Manual>Alarm>Motion detection>Timing                      |
| Local Playback               | 8CH (analog input mode)                                   |
| Search Mode                  | Search by time, calendar, event, channel                  |
| <b>Storage &amp; backup</b>  |   |
| Video Storage                | HDD, Network  |
| Backup Mode                  | Network, USB hard disk, USB burner, SATA burner           |
| <b>External Interface</b>    |   |
| Video Input                  | 8CH BNC   |
| Video Output                 | 1CH VGA, 1ch HDMI   |
| Audio I/O                    | 4/1   |
| Network Interface            | RJ45 10M/100M self-adaption                               |
| PTZ Control                  | Support kinds of PTZ protocols                            |
| USB                          | 2* USB ports  |
| HDD                          | 1*SATA ports (Max 8TB/per)                                |
| <b>General</b>               |   |
| Power Supply                 | 12V/2A  |
| Power Consumption            | <15W (without HDD)  |
| Working Environment          | Temperature:0°C—+55°C, Humidity:10%—90%, Atm:86kpa—106kpa |
| <b>Camera</b>                |   |
|                              | <b>Metal Bullet*8PCS</b>                                  |
| Image Sensor                 | 1/2.7" CMOS Image Sensor                                  |
| Resolution                   | 1080P@25/30fps  |
| Effective Pixels             | 1920(H) × 1080(V)   |
| Resolution                   | AHD   |
| Video Standard               | PAL/NTSC  |
| Synchronization              | Inter-Sync  |
| IR Distance                  | 20-25m  |
| Lens                         | 3.6mm/2.0MP   |
| Day & Night mode             | External control  |
| Min. Illumination            | 0.01Lux/F1.2  |

|   |                                    |
|---|------------------------------------|
| UTC   | Support                            |
| OSD   | Support                            |
| WDR   | Digital WDR                        |
| S/N Ratio   | ≥58dB                              |
| Electronic Shutter                                  | AUTO 1/50(60)~1/50000s             |
| White Balance                                       | Auto                               |
| AGC   | Auto                               |
| Video Output  | AHD                                |
| Dynamic Range                                       | 60db                               |
| DNR   | 2D DNR                             |
| Type  | Outdoor Metal Bullet Camera        |
| Video Port  | BNC                                |
| Power Supply  | 12 V DC±10%                        |
| Lightning protection                                | Support                            |
| Power Consumption                                   | Max 4W                             |
| Working Humidity                                    | Relative humidity less than 90%    |
| Operating Temp                                      | -20°C to +50°C ( - 14°F to 122°F ) |
| Storage Temp.                                       | -40°C to +60°C ( -40°F to 140°F )  |
| <b>Package</b>                                      |                                    |
| 8CH 5 IN 1 XVR ( Mouse ,12V 2A Power Adaptor ) *1PC |                                    |
| 2.0MP IR Metal Bullet Camera * 8PCS                 |                                    |
| 15M BNC & Power Cable * 8PCS                        |                                    |
| 1 Split to 4 Power Line * 2PCS                      |                                    |
| 12V 2A Power Adaptor for Camera * 2PCS              |                                    |