

## VR-IP0H300-L4

360 Panaramic Wifi SD I TF Card Bulb Camera



Model Number	VR-IP0H300-L4
Camera	
Image Sensor	1/2.6" CMOS Image Sensor
Min. Illumination	Color: 0.1Lux @F1.2, B/W:0.01Lux with IR on
WDR	ON/OFF
Lens	360 Degree lens
Shutter Time	default
LED (with Detecting Function)	3 PCS White LEDs and 3PCS IR LEDs, White LEDs will auto-turn on when detecting people around while IR on
IR Distance	10M
BLC	Default
HLC	Default
Video	
Max Image Resolution	1536*1536@20fps
Frame Rate	Main stream: 1536*1536
Video Compression	Support H.264 Main Profile & H.264 Baseline
Video Bit Rate	32Kbps-6144Kbps support self-adjustable, default 1536Kbps

Image Settings	Brightness, Contrast, Saturation, Exposure Adjustable
Bit Superposition	Support OSD name, time and date information superposition
<b>Audio</b>	
Audio I/O	Two-way audio, built-in microphone and speaker
Audio Compression	G.711
<b>Network</b>	
Communication	NO
Network Protocols	TCP/IP,ARP,IGMP,SMTP,FTP,DHCP,DNS, DDNS,NTP,UPNP,RTSP
Wifi	Wifi 802.11b/g/n
ONVIF	ONVIF2.4
<b>System</b>	
Alarm I/O	Motion detection Alarm
Storage	Max support 128G SD card, timing video storage, motion detection video storage
Motion Detection	4 windows motion detection areas can be setting (sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox, the picture and video be upload to FTP server
APP	Support android, IOS
<b>General</b>	
Working Temperature	-10°C-60°C
Working Humidity	10-95%(Non-condensing)
Interface type	E27
Power Supply	AC 100-240v 50-60Hz
Power Consumption	Max 6W
Working Humidity	Relative humidity less than 90%
Language Support	CHN(S)/ENG
Cover Color	White