

Wifi Standalone PTZ SD I TF Card Camera(Auto-focus 4x Zoom)

KEY FEATURES

- Support WI-Fi
- 5X optical Zoom 2.7~13.5mm
- Support max 128GB SD card
- Microphone inside monitor voice,two-way audio
- Vertical 90 horizontal 355
- Plug and play 24hours monitor
- IP66
- 50m IR distance 6pcs leds
- Easy to install
- CMS and mobile App management
- Options: POE I 6~22mm Lens I Outside Speaker



MP-B301I133M-WTA

- 1.3MP 1/3" CMOS,Hisilicon DSP
- H.264 encoding,960P@25fps
- Support 1pc SD/TF card Max 64GB

MP-B301I212M-WTA

- 2.0MP 1/2.9" SONY CMOS
- H.264 encoding,1080P@20fps
- Support 1pc SD/TF card Max 64GB

360 Degree Wifi Panoramic SD I TF Card Camera

KEY FEATURES

- Field angle:horizontal 182°/vertical 185°
- Video encode:AAC/G.711,Support two-way voice intercom
- Build-in 3pcs Array IR LED lamp,acoustic control networking
- Wireless standards:IEEE802.11b/g/n
- Storage interface:1 TF (Micro SD) storage interface,max64G
- Support AP model,Smart IR ,Motion detection
- Support P2P,CMS



VR-T1E4I132-WTA2

- 1.3MP 1/3" CMOS
- H.264 encoding,960P@20fps
- Support 1pc SD/TF card Max 64GB
- DC5V,1A

VR-T1E4I300-WTA2

- 3.0MP 1/2.6" CMOS,Hisilicon DSP
- H.264 encoding,3.0MP@20fps
- Support 1pc SD/TF card Max 64GB
- DC5V,1A

VR-T1G4I132-WTA2

- 1.3MP 1/3" CMOS
- H.264 encoding,960P@20fps
- Support 1pc SD/TF card Max 64GB
- DC12V,2A

VR-T1G4I205-WTA2

- 2.0MP 1/2.7" CMOS,Hisilicon DSP
- H.264 encoding,1080P@20fps
- Support 1pc SD/TF card Max 64GB
- DC12V,2A

VR-T1G4I300-WTA2

- 3.0MP 1/2.6" CMOS,Hisilicon DSP
- H.264 encoding,3.0MP@20fps
- Support 1pc SD/TF card Max 64GB
- DC12V,2A

KEY FEATURES

- Field angle:horizontal 182°/vertical 185°
- Video encode:AAC/G.711,Support voice pick up
- Build-in 6pcs Array IR LED lamp, acoustic control networking
- Wireless standards:IEEE802.11b/g/n
- Storage interface:1 TF (Micro SD) storage interface,max64G
- Support AP model, Smart IR ,Motion detection
- IP66



MP-T1C4I205-WTA2

- 1.3MP 1/3" CMOS
- H.264 encoding,960P@20fps
- Support 1pc SD/TF card Max 64GB
- DC12V,2A

MP-T1C4I300-WTA2

- 3.0MP 1/2.6" CMOS,Hisilicon DSP
- H.264 encoding,3.0MP@20fps
- Support 1pc SD/TF card Max 64GB
- DC12V,2A

Smart Wifi Robot Camera

KEY FEATURES

- Image resolution:720P/1080P
- Built-in microphone and speaker,two-way audio
- Day and night switch color/black and white
- Build-in11pcs IR LED lamp,acoustic control networking
- View Angle: Horizontal 120°/Vertical 70°
- Horizontal rotation 355°,Vertical rotation 90°
- Wireless standards: IEEE802.11 b/g/n
- Frequency range: 2.4 GHz ~ 2.4835 GHz
- Storage interface:1 TF (Micro SD) storage interface,max128G
- Support motion detection alarm
- RJ59 internet interface
- Power Supply :DC5V,<2A



MP-IP2H10-K6

- 1.0MP 1/4" CMOS
- H.264 encoding,720P@20fps
- Support 1pc SD/TF card Max 128GB

MP-IP2H20-K6

- 2.0MP 1/2.7" CMOS
- H.264 encoding,1080P@20fps
- Support 1pc SD/TF card Max 128GB

Smart 4G Bullet Camera

KEY FEATURES

- Indoor and Outdoor 4G Camera
(US Standard,suitable for South America,North America area,etc)
- 4G FDD-LTE: B1/B2/B4/B5/B12/B13/B17/B25/B26
- 3G WCDMA: B2/B4/ B5
- 2G GSM/EDGE: 1800MHZ/900MHZ
- Image resolution:1.0MP/2.0MP
- H.264/H.265 encoding,(H.265 for model MP-L1K5I216-G2TA2)
- Support two way audio,built-in speaker/Microphone
- Support motion detection alarm
- Fix lens;Super night vision;Hotspot AP
- Storage interface:1 TF(Micro SD)storage interface,,max64G/128G
- Support dual-stream simultaneously monitoring
- Support manual setting time zone of phone and synchronize to device
- Support Max 6users browsing at the same time (each stream:3 users)
- Support CMS,P2P,IP67



MP-L1K4I103-G2TA2	MP-L1K4I206-G2TA2	MP-L1K4I205-G2TA2	MP-L1K4I212-G2TA2	MP-L1K4I213-G2TA2	MP-L1K5I216-G2TA2
<ul style="list-style-type: none"> · 1.0MP 1/4" CMOS · H.264 encoding;720P @20fps · Support 1pc SD/TF card Max 64GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.7" CMOS · H.264 encoding,1080P @20fps · Support 1pc SD/TF card Max 64GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.7" CMOS, Hisilicon DSP · H.264 encoding,1080P @20fps · Support 1pc SD/TF card Max 64GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.9" SONY CMOS, Hisilicon DSP · H.264 encoding,1080P @20fps · Support 1pc SD/TF card Max 64GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.9" SONY CMOS, Hisilicon DSP · H.264 encoding,1080P @25/30fps · Support 1pc SD/TF card Max 128GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.8" SONY CMOS (can be Starlight),Hisilicon DSP · H.265/H.264 encoding, 1080P@20fps · Support 1pc SD/TF card Max 64GB

KEY FEATURES

- Indoor and Outdoor 4G Camera
- Image resolution:1.0MP/2.0MP
- H.264/H.265 encoding
- Built-in Microphone,with audio
- Support motion detection alarm
- Fix lens;Super night vision;Hotspot AP
- Storage interface:1 TF(Micro SD)storage interface,,max64G/128G
- Support dual-stream simultaneously monitoring
- Support manual setting time zone of phone and synchronize to device
- Support Max 6users browsing at the same time (each stream:3 users)
- Support CMS,P2P,IP67



MP-L8Q4I103-G1TA MP-L8Q4I103-G2TA	MP-L8Q4I206-G1TA MP-L8Q4I206-G2TA	MP-L8Q4I205-G1TA MP-L8Q4I205-G2TA	MP-L8Q4I212-G1TA MP-L8Q4I212-G2TA	MP-L8Q4I213-G1TA MP-L8Q4I213-G2TA	MP-L8Q5I216-G1TA MP-L8Q5I216-G2TA
<ul style="list-style-type: none"> · 1.0MP 1/4" CMOS · H.264 encoding;720P @20fps · Support 1pc SD/TF card Max 64GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.7" CMOS · H.264 encoding,1080P @20fps · Support 1pc SD/TF card Max 64GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.7" CMOS, Hisilicon DSP · H.264 encoding,1080P @20fps · Support 1pc SD/TF card Max 64GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.9" SONY CMOS, Hisilicon DSP · H.264 encoding,1080P @20fps · Support 1pc SD/TF card Max 64GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.9" SONY CMOS, Hisilicon DSP; · H.264 encoding,1080P @25/30fps; · Support 1pc SD/TF card Max 128GB 	<ul style="list-style-type: none"> · 2.0MP 1/2.8" SONY CMOS (can be Starlight),Hisilicon DSP; · H.265/H.264 encoding,1080P @20fps; · Support 1pc SD/TF card Max 64GB

- (Europe Standard,suitable for Asia,Africa,Europe Countries,etc)
- 4G FDD-LTE : B1/B3/B7/B8/B20
 - 4G TDD-LTE: B38/B40/B41
 - 3G WCDMA: B1/B8
 - 2G GSM/EDGE: 1800MHZ/900MHZ

- (US Standard,suitable for South America,North America area,etc)
- 4G FDD-LTE: B1/B2/B4/B5/B12/B13/B17/B25/B26
 - 3G WCDMA: B2/B4/ B5
 - 2G GSM/EDGE: 1800MHZ/900MHZ

4G Router

KEY FEATURES

- 3G 4G Wireless Router
- Support 3G 4G switch to Wired or Wifi
- Support global networkTDD-LTE/FDD-LTE/UMTS/TD-SCDMA/EVDO,etc
- Support wifi 802.11b/g/n
- WiFi MIMO 2*2,up to 300Mbps
- LTE CAT4 MIMO 2*2,up to 150Mbps
- 2*RJ45 LAN(POE 48V optional)
- Built-in wifi and 4G antenna
- Support 32pcs WIFI users
- IP66

MP-4GRL2-B



KEY FEATURES

- 3G 4G Wireless Router
- Support 3G 4G switch to Wired or Wifi
- 2pcs antenna(1xwifi,1x4G);1*RJ45 LAN
- Support wifi 802.11b/g/n
- Wifi access bandwidth 10-40MHZ (Default=20MHZ)
- 10-50M open space with no obstacles
- 12V 1.5A

MP-4GRL1-A



Smart 4G PTZ Camera and Solar Kit

KEY FEATURES

- 7 Inch Outdoor 4G Speed Dome Camera
- Image resolution:1/2.8" SONY Sensor,2.0MP
- 20X Optical Zoom,4.7mm~94mm,H.264 encoding
- 360° all-frame endless rotation
- External WiFi antenna+ External 4G antenna
- Horizontal Rotation Speed 0.1° ~ 40°/s, Vertical rotation speed 0.1° ~ 40°/s
- Wi-Fi/802.11/b/g/n, PC CMS to control multi-cameras
- Support Power off memory/128 Presets point/4 groups cruise/A-B scan/360° auto-scan
- 5pcs Smart IR Array LEDs + 3pcs Laser LEDs,IR Distance 150M
- Breakage self-test repair,auto-check and recover connection every two minutes
- Support motion detection alarm;Hotspots,CMS,P2P,ONVIF
- Support 1 TF(Micro SD)storage interface,max64G
- Manually setting time zone of phone and synchronize to device
- IP66,12V 4A,Lighting protection:6000V



MP-B604I212H2-G1T	MP-B604I212H2-G2T
(Europe Standard,suitable for Asia,Africa,Europe Countries,etc) · 4G FDD-LTE: B1/B3/B7/B8/B20 · 4G TDD-LTE: B38/B40/B41 · 3G WCDMA: B1/B8 · 2G GSM/EDGE: 1800MHZ/900MHZ	(US Standard,suitable for South America,North America area,etc) · 4G FDD-LTE: B1/B2/B4/B5/B12/B13/B17/B25/B26 · 3G WCDMA: B2/B4/ B5 · 2G GSM/EDGE: 1800MHZ/900MHZ

MP-B604I212H2-G1TS

- Outdoor 4G Speed Dome Camera(EU Standard) (Model:MP-B604I212H2-G1T)
- 50W monocrystalline silicon high efficiency solar panel + 12V30AH lithium battery

MP-B604I212H2-G2TS

- Outdoor 4G Speed Dome Camera(US Standard) (Model:MP-B604I212H2-G2T)
- 50W monocrystalline silicon high efficiency solar panel + 12V30AH lithium battery



- 1080P 4G Camera with Solar Panel Set
- Image Resolution: 1.0MP/1.3MP/2.0MP
- H.264 encoding
- Support manual setting time zone of phone and synchronize to device
- Support motion detection alarm
- Fix lens;2pcs IR array leds,Super night vision
- Storage interface:1 TF(Micro SD)storage interface,ma128G
- Support dual-stream simultaneously monitoring
- Support manual setting time zone of phone and synchronize to device
- Support CMS,P2P,Hotspot AP,IP66
- 60W monocrystalline silicon high efficiency solar panel + 12V 30AH lithium battery

4G STANDALONE SOLAR CAMERA SYSTEM

- Cable
- Internet
- Electricity
- DVR/NVR



Farm



Scenic Area



Mountain area



Highway



Desert

MP-D2E10M-TWS	MP-D2E13M-TWS	MP-D2E20M-TWS
1.0MP	1.3MP	2.0MP

Battery Wifi/4G Camera



MP-BC5



Portable Mini battery wifi Camera

- Image resolution:1080p,outdoor indoor use,H.264
- Powered by 400 Ma lithium battery,2 hours continue working time
- Support Wi-Fi 802.11 b/g/n,AP hotspot
- G726, G711, AAC, MP3 format, 8K sampling rate, support echo cancellation function
- IR distance 10m
- Built-in mic,support audio recording
- Up to 64gb tf card , recording video 7days
- Support mobile alarming,motion detection
- Support dual-stream simultaneously monitoring
- Support CMS,P2P



MP-BC2



Multi-function Two in One Wifi Doorbell Camera

- Image resolution:1080P ,2.0MP
- Powered by 7650 Ma polymer lithium ion battery,charge voltage: 5v2a
- Pure battery standby time more than 180 days
- Support Wi-Fi 802.11 b/g/n
- G726, G711, AAC, MP3 format, 8K sampling rate, support echo cancellation function
- PIR Human Temperature Detection,PIR alarm push
- Two-way audio,with auto cancellation;built-in speaker/Microphone
- Storage interface:1 TF(Micro SD)storage interface,max32GB
- Support dual-stream simultaneously monitoring
- Support CMS,P2P
- IP66



MP-BC1



Solar Wifi Battery camera

- Image resolution:1080P ,2.0MP
- Solar power board anti-wear and scratch resistant
- Powered by 6600 Ma polymer lithium battery
- Pure battery standby time more than 150 days
- Support Wi-Fi 802.11 b/g/n
- G726, G711, AAC, MP3 format, 8K sampling rate, support echo cancellation function
- PIR Human Temperature Detection,PIR alarm push
- Two-way audio,with auto cancellation;built-in speaker/Microphone
- Storage interface:1 TF(Micro SD)storage interface,max32GB
- Support dual-stream simultaneously monitoring
- Support CMS,P2P
- IP66

KEY FEATURES

All-weather WiFi Battery Camera

- Image resolution:1080P ,2.0MP
- Charge voltage: 5v2a
- Support Wi-Fi 802.11 b/g/n
- G726, G711, AAC, MP3 format, 8K sampling rate, support echo cancellation function
- PIR Human Temperature Detection,PIR alarm push
- Two-way audio,with auto cancellation;built-in speaker/Microphone
- Storage interface:1 TF(Micro SD)storage interface,max64GB
- Support dual-stream simultaneously monitoring
- Support CMS,P2P
- IP66



MP-BC3

- 5200 Ma lithium polymer battery
- Pure battery standby time more than 180 days

MP-BC4

- 10400 ma polymer lithium battery
- Pure battery standby time more than 360 days

KEY FEATURES

All-weather Solar Battery Camera

- Image resolution:1080P ,2.0MP
- Solar power board anti-wear and scratch resistant
- Powered by3pcs 18650 lithium battery
- Pure battery standby time more than 150 days
- G726, G711, AAC, MP3 format, 8K sampling rate, support echo cancellation function
- PIR Human Temperature Detection 10m,PIR alarm push
- Two-way audio,with auto cancellation;built-in speaker/Microphone
- Storage interface:1 TF(Micro SD)storage interface,max32GB,recording video 80hours
- Support recording when network is not available suddedly,PIR alarm info sent ,can check the recording after network is on
- Support dual-stream simultaneously monitoring
- Support CMS,P2P
- IP66,Industrial plastic case



MP-BC6

- Solar Wifi Battery camera
- Wi-Fi 802.11 b/g/n

MP-BC7

- Solar 4G Battery camera

SMART HOME SERIES - Speical Wifi Camera

Speical Wifi Hidden Camera



MP-H1	MP-H2	MP-H4
<ul style="list-style-type: none"> 1080P Hidden Belt Camera H.264,plug and play,P2P;Max 128G TF card Wifi 802.11b/g/n Built-in battery,3-5 hours working time once full charged Support all kinds of shooting and recording Fast Remote Playback and motion alarm Support TUTK 	<ul style="list-style-type: none"> 1080P Hidden Clock Camera H.264,plug and play,P2P;Max 128G TF card IR distance 5-8m Wifi 802.11b/g/n Built-in battery,10 hours working time once full charged Support always plugged in and powered Fast Remote Playback and motion alarm 5V 2A Support TUTK 	<ul style="list-style-type: none"> 1080P Hidden Clock Camera H.264,plug and play,P2P;Max 128G TF card IR distance 5-8m Wifi 802.11b/g/n Built-in battery,10 hours working time once full charged Support always plugged in and powered Fast Remote Playback and motion alarm 5V 2A Support TUTK



MP-H5	MP-H3
<ul style="list-style-type: none"> 1080P Hidden Mini Camera H.264,plug and play,P2P;Max 128G TF card Wifi 802.11b/g/n,AP hotspot Built-in battery,5.5 hours working time once full charged Fast Remote Playback and motion alarm Built-in magnet,with 360° rotation bracket Support TUTK 	<ul style="list-style-type: none"> 1080P Hidden Plug Camera H.264,plug and play,P2P;Max 128G TF card IR distance 5-8m Wifi 802.11b/g/n Working once plug in Fast Remote Playback and motion alarm 5V 2A Support TUTK

Smart Fingerprint Padlock



- Fingerprint Recognizer
- 2 Years
- USB charge

MP-FR360-D2
<ul style="list-style-type: none"> Support 2 administrators,total 10 fingerprints Low power consumption and long standby time. With 1 piece 240MAH lithium polymer battery, can be unlocked 1000 times when fully charged. Support 360 Degree Fingerprint Recognize IP66 waterproof level USB charge Unlock time less than 300ms

Smart Home Wifi Camera



Smart WIFI Robot Camera

- Image resolution 720P/1080P
- Built-in microphone and speaker,two-way audio
- Day and night switch color/black and white
- View Angle: Horizontal 120°/Vertical 70°
- Horizontal rotation 355°,Vertical rotation 90°
- Wireless standards: IEEE802.11 b/g/n
- Storage interface:1 TF(Micro SD)storage interface,max128G
- Support motion detection alarm
- RJ59 internet interface
- DC5V 2A



MP-IP1P10-K7 (720P)

MP-IP1P20-K7 (1080P)

HD 4CH/8CH AHD XVR Kit

4CH 5 IN 1 XVR KIT

- 4pcs Plastic Dome Camera
- 1PC XVR 5 IN 1
- 4PCS 15M cable
- 1PC 1 to 4 splitter DC cable
- 1PC 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25M IR Distance



4CH 5 IN 1 XVR KIT

- 4pcs Plastic Bullet Camera
- 1PC XVR 5 IN 1
- 4PCS 15M All in one cable
- 1PC 1 to 4 splitter DC cable
- 1PC 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 35M IR Distance



LM5104Q2EQ2EA101 1.0MP

LM5104Q2EQ2EA206 2.0MP

LM5104P1AP1AA101 1.0MP

LM5104P1AP1AA206 2.0MP

MH8104Q2EQ2A500 5.0MP

MH5104P1AP1AA500 5.0MP

4CH 5 IN 1 XVR KIT

- 2pcs Plastic Bullet Camera
- 2pcs Plastic Dome Camera
- 1PC XVR 5 IN 1
- 4PCS 15M All in one cable
- 1PC 1 to 4 splitter DC cable
- 1PC 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25/35M IR Distance



4CH 5 IN 1 XVR KIT

- 2pcs Metal Bullet Camera
- 2pcs Plastic Dome Camera
- 1PC XVR 5 IN 1
- 4PCS 15M All in one cable
- 1PC 1 to 4 splitter DC cable
- 1PC 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25M IR Distance



LM5104P1AQ2EA101 1.0MP

LM5104P1AQ2EA206 2.0MP

LM5104L1MQ2EA101 1.0MP

LM5104L1MQ2EA206 2.0MP

MH8104P1AQ2EA500 5.0MP

MH8104L1MQ2EA500 5.0MP

4CH 5 IN 1 XVR KIT

- 4pcs Metal Bullet Camera
- 1PC XVR 5 IN 1
- 4PCS 15M All in one cable
- 1PC 1 to 4 splitter DC cable
- 1PC 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25M IR Distance



4CH 5 IN 1 XVR KIT

- 4pcs Metal Dome Camera
- 1PC XVR 5 IN 1
- 4PCS 15M All in one cable
- 1PC 1 to 4 splitter DC cable
- 1PC 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25M IR Distance



LM5104L1ML1MA101 1.0MP

LM5104L1ML1MA206 2.0MP

LM5104M1AM1AA101 1.0MP

LM5104M1AM1AA206 2.0MP

MH8104L1ML1MA500 5.0MP

MH8104M1AM1AA500 5.0MP

4CH 5 IN 1 XVR KIT

- 2pcs Metal Bullet Camera
- 2pcs Metal Dome Camera
- 1PC XVR 5 IN 1
- 4PCS 15M All in one cable
- 1PC 1 to 4 splitter DC cable
- 1PC 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25M IR Distance



8CH 5 IN 1 XVR KIT

- 8pcs Plastic Dome Camera
- 1PC XVR 5 IN 1
- 8PCS 15M All in one cable
- 2PCS 1 to 4 splitter DC cable
- 2PCS 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25M IR Distance



LM5104M1AL1MA101 1.0MP

LM5104M1AL1MA206 2.0MP

LM5108Q2EQ2EA101 1.0MP

LM5108Q2EQ2EA206 2.0MP

MH8104M1AL1MA500 5.0MP

ME8108Q2EQ2EA500 5.0MP

8CH 5 IN 1 XVR KIT

- 8pcs Plastic Bullet Camera
- 1PC XVR 5 IN 1
- 8PCS 15M All in one cable
- 2PCS 1 to 4 splitter DC cable
- 2PCS 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 35M IR Distance



8CH 5 IN 1 XVR KIT

- 4pcs Palstic Bullet Camera
- 4pcs Plastic Dome Camera
- 1PC XVR 5 IN 1
- 8PCS 15M All in one cable
- 2PCS 1 to 4 splitter DC cable
- 2PCS 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25/35M IR Distance



LM5108P1AP1AA101 1.0MP

LM5108P1AP1AA206 2.0MP

LM5108P1AQ2EA101 1.0MP

LM5108P1AQ2EA206 2.0MP

ME8108P1AP1AA500 5.0MP

ME8108P1AQ2EA500 5.0MP

8CH 5 IN 1 XVR KIT

- 4pcs Metal Bullet Camera
- 4pcs Plastic Dome Camera
- 1PC XVR 5 IN 1
- 8PCS 15M All in one cable
- 2PCS 1 to 4 splitter DC cable
- 2PCS 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25M IR Distance



8CH 5 IN 1 XVR KIT

- 8pcs Metal Dome Camera
- 1PC XVR 5 IN 1
- 8PCS 15M All in one cable
- 2PCS 1 to 4 splitter DC cable
- 2PCS 12V 2A Power adaptor
- Intallation accessories
- 3.6mm 25M IR Distance



LM5108L1MQ2EA101 1.0MP

LM5108L1MQ2EA206 2.0MP

LM5108M1AM1AA101 1.0MP

LM5108M1AM1AA206.0MP

ME8108L1MQ2EA500 5.0MP

ME8108M1AM1AA500 5.0MP

HD 4CH/8CH AHD XVR Kit

- 8CH 5 IN 1 XVR KIT
- 8pcs Metal Bullet Camera
 - 1PC XVR 5 IN 1
 - 8PCS 15M All in one cable
 - 2PC 1 to 4 splitter DC cable
 - 2PC 12V 2A Power adaptor
 - Intallation accessories
 - 3.6mm 25M IR Distance



- 8CH 5 IN 1 XVR KIT
- 4pcs Metal Bullet Camera
 - 4pcs Plastic Dome Camera
 - 1PC XVR 5 IN 1
 - 8PCS 15M All in one cable
 - 2PC 1 to 4 splitter DC cable
 - 2PC 12V 2A Power adaptor
 - Intallation accessories
 - 3.6mm 25M IR Distance



LM5108L1ML1MA101 1.0MP

LM5108L1ML1MA206 2.0MP

LM5108M1AL1MA101 1.0MP

LM5108M1AL1MA206 2.0MP

ME8108L1ML1MA500 5.0MP

ME8108M1AL1MA500 5.0MP

HD 4CH/8CH POE NVR Kit

- 52V 4CH POE KIT
- 4PCS Metal bullet poe camera
 - 1set 4ch POE NVR
 - 1pc 52V 1.5A power adaptor
 - 1 USB Mouse
 - 1pc 1meter NETWORK Cable+4pcs 20m network cable
 - 2.0MP/5.0MP 3.6mm 25M IR Distance



- 52V 8CH POE KIT
- 8PCS Metal bullet poe camera
 - 1set 8ch POE NVR
 - 1pc 52V 1.5A power adaptor
 - 1 USB Mouse
 - 1pc 1meter NETWORK Cable+8pcs 20m network cable
 - 2.0MP/5.0MP 3.6mm 25M IR Distance



NVR204PL1ML1ME201 2.0MP

NVR204PL1ML1ME500 5.0MP

NVR208PL1ML1ME201 2.0MP

NVR208PL1ML1ME500 5.0MP

HD 4CH/8CH Wifi Kit

- 4CH Wifi NVR KIT
- 4pcs Metal Bullet Camera
 - 1PC Wifi NVR 4CH
 - 4PCS 1A Adaptor
 - Intallation accessories
 - 1.0MP/H.265 2.0MP
 - 3.6mm 30M IR Distance



- 8CH Wifi NVR KIT
- 8pcs Metal Bullet Camera
 - 1PC Wifi NVR 8CH
 - 8PCS 1A Adaptor
 - Intallation accessories
 - 1.0MP/H.265 2.0MP 3.6mm 30M IR Distance



AH6104L3QJ100-W 1.0MP

AH6104L3QJ200-W 2.0MP

AH6108L3QJ100-W 1.0MP

AH6108L3QJ200-W 2.0MP

- 4CH Wifi NVR KIT
- 4pcs Metal Bullet Camera
 - 1PC Wifi NVR 4CH
 - 4PCS 1A Adaptor
 - Intallation accessories
 - 1.0MP/H.265 2.0MP
 - 3.6mm 30M IR Distance



- 8CH Wifi NVR KIT
- 4pcs Metal Bullet Camera
 - 1PC Wifi NVR 4CH
 - 4PCS 1A Adaptor
 - Intallation accessories
 - 1.0MP/H.265 2.0MP
 - 3.6mm 30M IR Distance



AH6104L3QJ101-W 1.0MP

AH6104L3QJ201-W 2.0MP

AH6108L3QJ101-W 1.0MP

AH6108L3QJ201-W 2.0MP

- 4CH Wifi NVR KIT
- 4pcs Metal Bullet Camera
 - 1PC Wifi NVR 4CH
 - 4PCS 1A Adaptor
 - Intallation accessories
 - 1.0MP/H.265 2.0MP
 - 3.6mm 40M IR Distance



- 8CH Wifi NVR KIT
- 8pcs Metal Bullet Camera
 - 1PC Wifi NVR 8CH
 - 8PCS 1A Adaptor
 - Intallation accessories
 - 1.0MP/H.265 2.0MP
 - 3.6mm 40M IR Distance



AH6104L2JJ100-W 1.0MP

AH6104L2JJ200-W 2.0MP

AH6108L2JJ100-W 1.0MP

AH6108L2JJ200-W 2.0MP

- 4CH Wifi NVR KIT
- 4pcs Metal Bullet Camera
 - 1PC Wifi NVR 4CH
 - 4PCS 1A Adaptor
 - Intallation accessories
 - 1.0MP/H.265 2.0MP
 - 3.6mm 40M IR Distance



- 8CH Wifi NVR KIT
- 8pcs Metal Bullet Camera
 - 1PC Wifi NVR 8CH
 - 8PCS 1A Adaptor
 - Intallation accessories
 - 1.0MP/H.265 2.0MP
 - 3.6mm 40M IR Distance



AH6104L2JJ101-W 1.0MP







AH6104L2JJ201-W 2.0MP

AH6108L2JJ101-W 1.0MP

AH6108L2JJ201-W 2.0MP

VEHICLE SERIES- Car Camera

HD Analogue | 4G Car Camera

	C1JH130F2-YC,960P		C2AMC700F-C,700TVL		C2A13M-GT,960P 4G
	C1JH207F2-YC,1080P		C2AMC120F-C,1000TVL		C2A20M-GT,1080P 4G
<ul style="list-style-type: none"> - Dual Eyes Indoor Case, front lens 3.6/6mm optional, inside lens 1.8mm fixed, - with 15pcs 940nm ir led, hidden led, inside 170degree 		<ul style="list-style-type: none"> - Metal X-man Case, IP67/68K - 2.8/3.6/6mm optional 		<ul style="list-style-type: none"> - Metal X-man Case, 4G, IP67/68K - 2.8/3.6/6mm optional 	
	C1BMC700F-C,700TVL		C1HMC700F-C,700TVL		C2EMC700F-C,700TVL
	C1BMC120F-C,1000TVL		C1HMC120F-C,1000TVL		C2EMC120F-C,1000TVL
	C1BH100F-C,720P		C1HH100F-C,720P		C2EH100F-C,720P
	C1BH130F-C,960P		C1HH130F-C,960P		C2EH130F-C,960P
	C1BH207F-C,1080P		C1HH207F-C,1080P		C2EH207F-C,1080P
	C1BH202F-C,1080P		C1HH202F-C,1080P		C2EH202F-C,1080P
<ul style="list-style-type: none"> - Metal Eyebow Case ,IP67/68K - 2.8/3.6/6mm optional 		<ul style="list-style-type: none"> - Metal Dome Case, IP67/68K - 2.8/3.6/6mm optional 		<ul style="list-style-type: none"> - Plastic Dome Case, - 2.8/3.6/6mm optional 	



Mobile DVR

960P AHD Single SD card Mobile DVR



- Only 15s fast system-In H264 SD CARD AHD Mobile DVR
- Real-time,960p/720p/D1/CIF are optional,frame is adjustable,support analoge&AHD mixed
- Hisilicon 3520DV200,4/8 Channel optional Build in stable linux system
- Professional RAW-Device,Multi language optional(english,russian,korean)also support customized language
- Action with alarm,device with 4ch alarm input&2ch alarm output
- Multiple recording methods,Automatic recording,Manual recording and alarming recording
- Parking recording can be max 1440mins
- Power output for cameras(12V),10V~36V wide voltage design
- Support low voltage automatically turn-off the mobile DVR can protect well the battery
- USB port plus USB back-up function,suport VGA output,Din-connector
- Recording Automatic coverage,Max support 256GB SD card
- Support video output (mirro,erect,left,right video)

MAVR104A-M1	MAVR108A-M1
4ch	8ch

960P AHD Hard Drive Mobile DVR



- Only 15s fast system-In H264 SD CARD AHD Mobile DVR
- Real-time,960p/720p/D1/CIF are optional,frame is adjustable,support analoge&AHD mixed
- Hisilicon 3520DV200,4/8 Channel optional Build in stable linux system
- Professional RAW-Device,Multi language optional(english,russian,korean)also support customized language
- Action with alarm,device with 4ch alarm input&2ch alarm output
- Multiple recording methods,Automatic recording,Manual recording and alarming recording
- Parking recording can be max 1440mins
- Power output for cameras(12V),10V~36V wide voltage design
- Support low voltage automatically turn-off the mobile DVR can protect well the battery
- USB port function,suport VGA output,Din-connector
- USB back-up function need customized
- Recording Automatic coverage,Max 2TB 2.5inch HDD,5400ram hard drive less than 1A
- Support video output (mirro,erect,left,right video)
- 3G/4G/WIFI Support remote video monitor,and remote download video file,intercom fuction need download cms and mobile app

MAVR104A-M2	MAVR104D-M2	MAVR108A-M2	MAVR108D-M2
4ch basic	4ch WIFI+4G+GPS	8ch basic	8ch WIFI+4G+GPS

1080P AHD Hard Drive Mobile DVR



- Only 15s fast system-In H264 SD CARD AHD Mobile DVR
- Real-time,1080/960p/720p/D1/CIF are optional,frame is adjustable,support analoge&AHD mixed
- Hisilicon 3520DV300,4/8 Channel optional Build in stable linux system
- Professional RAW-Device,Multi language optional(english,russian,korean)also support customized language
- Action with alarm,device with 4ch alarm input&2ch alarm output
- Multiple recording methods,Automatic recording,Manual recording and alarming recording
- Parking recording can be max 1440mins
- Power output for cameras(12V),10V~36V wide voltage design
- Support low voltage automatically turn-off the mobile DVR can protect well the battery
- USB port function,suport VGA output,Din-connector
- USB back-up function need customized
- Recording Automatic coverage,Max 2TB 2.5inch HDD,5400ram hard drive less than 1A
- Support video output (mirro,erect,left,right video);
- Support power off video protection;
- 3G/4G/WIFI Support remote video monitor,and remote download video file,intercom fuction need download cms and mobile app

MAVR104A-H2	MAVR104D-H2	MAVR108A-H2	MAVR108D-H2
4ch basic	4ch WIFI+4G+GPS	8ch basic	8ch WIFI+4G+GPS

1080P AHD Dual-SD Card Mobile DVR



- Only 15s fast system-In H264 SD CARD AHD Mobile DVR
- Real-time,1080/960p/720p/D1/CIF are optional,frame is adjustable,support analoge&AHD mixed
- Hisilicon 3520DV300,4/8 Channel optional Build in stable linux system;
- Professional RAW-Device,Multi language optional(english,russian,korean)also support customized language
- Action with alarm,device with 4ch alarm input&2ch alarm output
- Multiple recording methods,Automatic recording,Manual recording and alarming recording;
- Parking recording can be max 1440mins;
- Power output for cameras(12V),10V~36V wide voltage design;
- Support low voltage automatically turn-off the mobile DVR can protect well the battery;
- USB port function plus USB Back-up,suport VGA output, Din-connector;
- Recording Automatic coverage,Max support 256GB SD card
- Support video output (mirro,erect,left,right video);
- Support power off protection;
- Support power off video protection;
- 3G/4G/WIFI Support remote video monitor,and remote download video file,intercom fuction need download cms and mobile app

MAVR104D-H3	MAVR108A-H3	MAVR108D-H3
4ch WIFI+4G+GPS	8ch basic	8ch WIFI+4G+GPS

Mobile DVR, POE NVR

1080N/1080P 4CH | 8CH AHD HDD Mobile DVR



- 4CH 4*1080P/8CH 8*1080N or 2CH 1080P+6CH 1080N
- Graphical menu(OSD menu); User password & Admin password separately; embedded Linux operation system
- 8channels 1080N HD video input, 1 channel video sync-output, 1 channel VGA output
- Support 2.5 inch HD, max to 2TB
- Support mouse operation
- Reversing mirror configuration
- Bad sector detection for SD card, ensure the constancy of video and life of SD card
- Built-in supercapacitor, avoiding data loss and disk damaged by abnormal power
- Support intelligent power management identification, automatic shutdown with low power, low power consumption flameout
- over capacity/ undervoltage/short circuit/ reserve voltage multi-protections, suit for various cars
- Support Unicom, Telecom and Mobile 3G/4G network; (Function type does not include location and network functions)
- WIFI OPTIOANL
- Support real time remote monitoring on computer and mobile(Android, APPLE system)
- Support global GPS location
- Built-in GPS function, can record tracks and speed of cars
- Playback on PC, tracks and speed of cars can be demonstrated on map
- Support playback and analyse on PC, local playback
- Support RJ45, 10M/100M self-adaptive Ethernet port
- Power input: 8~56V; voltage input: 12V/2A
- Operating temperature:-20 C --60 C

MXVR104A	MXVR104B	MXVR104C	MXVR104D
Basic	GPS+Wifi	4G+GPS	4G+GPS+WIFI
MXVR108A	MXVR108B	MXVR108C	MXVR108D
Basic	GPS+Wifi	4G+GPS	4G+GPS+WIFI

1080P HDD POE Mobile NVR



- 8ch HDD(Support 1PC)Network Mobile POE NVR, 8*1080P
- 8channels 1080P HD video input, 1 channel video sync-output, 1 channel VGA output
- Support 1 unit 2.5 inch HD (max to 2TB) and 1 SD card (max to 256G)
- Support mouse operation
- Reversing mirror configuration
- Bad sector detection for SD card, ensure the constancy of video and life of SD card
- Built-in supercapacitor, avoiding data loss and disk damaged by abnormal power
- Support intelligent power management identification, automatic shutdown with low power, low power consumption flameout
- over capacity/ undervoltage/short circuit/ reserve voltage multi-protections, suit for various cars
- Support Unicom, Telecom and Mobile 3G/4G network; (Function type does not include location and network functions)
- WIFI OPTIONAL
- Support real time remote monitoring on computer and mobile(Android, APPLE system)
- Support global GPS location
- Built-in switch, 4 channels aviation joint
- Built-in GPS function, can record tracks and speed of cars
- Playback on PC, tracks and speed of cars can be demonstrated on map
- Support playback and analyse on PC, local playback
- Support RJ45, 10M/100M self-adaptive Ethernet port
- Power input: 8~36V; voltage input: 12V/2A
- Operating temperature:-20 C --60 C
- 60mm*Size:148mm*188mm*60mm

MNVR208A	MNVR208B	MNVR208C	MNVR208D
Basic	GPS+Wifi	4G+GPS	4G+GPS+WIFI

Car System Accessories



MP-C1-5M 10M 15M 20M XX	MP-C0-3M 10M XX	MP-RS2-C2	MP-RS1-C	MP-704CA
· 4pin female to male din extender cable · 5M,10M,15M,20M,customized length acceptable	4pin female to male flexible din extender cable 3M,10M,customized length acceptable	2way radio speaker microphone support connect with walkie talkie	car radio speaker	7inch LCD



- High Efficiency
- Super Real time(60FPS)
- Ultra HLC
- Cost saving

SMART LICENSE PLATE CAMERA

Car License Plate Capture Camera

800TVL License Plate Capture Outdoor Waterproof Shield Camera (Under 30-50KM/H Speed)

- 1/3" Sony 960H high-performance CCD
- High definition 800TVL
- True Day/Night,Ultra Low illumination
- Super WDR,OSD menu,UTC,3DNR
- Up to 15M,4pcs White Leds
- Auto-Iris 6-60mm Lens
- Wide Voltage
- Surge protection
- 12VDC,Defog,HLC
- IP67



MP-H1BMD800V-L40

HD 2.1MP License Plate Capture Outdoor Waterproof Shield Camera (Under 30-50KM/H Speed)

- 1/2.8" Sony high-performance CMOS
- AHD/CVI/TVI/CVBS output,up to 5.0MP resolution
- True Day/Night,Ultra Low illumination
- Super WDR,OSD menu,UTC,3DNR
- Up to 40M,4pcs White Leds
- Wide Voltage,
- Surge protection
- 12VDC,Defog,HLC
- IP67



MP-H1BH212V-L40

HD 4.1MP License Plate Capture Outdoor Waterproof Shield Camera (Under 30-50KM/H Speed)

- 1/3" Sony high-performance CMOS
- AHD/CVI/TVI/CVBS output
- True Day/Night,Ultra Low illumination
- Super WDR,OSD menu,UTC,3DNR
- Up to 15M,4pcs White Leds
- Wide Voltage
- Surge protection
- 12VDC,Defog,HLC
- IP67



MP-H1BH411V-L40

HD Body Worn Camera

KEY FEATURES

- HD 2.0MP Body Worn Camera
- Up to 1920x1080 30fps video resolution, support audio recording
 - 2 inch TFT-LED high-resolution color display and playback
 - One-key recording and snap shot, Up to 30 million pixels resolution (8000x4500) for snap shot
 - 140 wide angle of view, 16X digital Zoom
 - Support night vision, up to 10 meters with visible face image, up to 20m with visible contour
White leds support lighting function at night
 - Built in 6000mAh battery capacity for 16 hours recording (less than 8 hours charging time) (P.S. 6 hours working time when there is no light with IR on)
 - Pre-record and Post-record; Multi-time period recording setting
 - Support encrypt recording video function
 - Built-in 32GB TF card standard (64GB, 128GB optional), recycle cover storage
 - One-key Important remark and Alarm flash, Super long watermark, file name setting, etc
 - Industrial plastic case and unique structure design, antidropping grade up to 2.5m
 - IP67 waterproof
 - Accessories: back clip, long shoulder clip, data cable, charger, CD, user manual



2MTA-L1

KEY FEATURES

- HD 2.0MP Body Worn Camera
- Up to 1920x1080 30fps video resolution, support audio recording
 - 2 inch TFT-LED high-resolution color display and playback
 - One-key recording and snap shot, Up to 36 million pixels resolution for snap shot
 - 140 wide angle of view, 16X digital Zoom
 - Support night vision, up to 6 meters with visible face image, up to 12m with visible contour
White leds support lighting function at night
 - Built in 3000mAh battery capacity for 15 hours recording (less than 4 hours charging time)
 - Pre-record and Post-record; Multi-time period recording setting
 - Laser positioning, fixed-point and position shooting to make sure the pic will not migrate
 - Support encrypt recording video function
 - Built-in 32GB TF card standard (64GB, 128GB optional), recycle cover storage
 - One-key Important remark and Alarm flash, Super long watermark, file name setting, etc
 - Industrial plastic case and unique structure design, antidropping grade up to 2.5m
 - Interface: USB2.0
 - IP66 waterproof
 - Accessories: back clip, long shoulder clip, data cable, charger, CD, user manual



2MT1A-L2

KEY FEATURES

- HD 3.0MP Body Worn Camera
- Up to 2304x1296P 30fps video resolution, support audio recording
 - 2 inch TFT-LED high-resolution color display and playback
 - One-key recording and snap shot, Up to 30 million pixels resolution for snap shot (auto/continuous)
 - 140 wide angle of view, 16X digital Zoom
 - Support night vision, up to 7 meters with visible face image, up to 10m with visible contour
White leds support lighting function at night
 - Built in 3000mAh battery capacity for 8 hours recording (less than 4 hours charging time)
 - Pre-record and Post-record; Multi-time period recording setting
 - Support encrypt recording video function
 - Built-in 32GB TF card standard (64GB, 128GB optional), recycle cover storage
 - One-key Important remark and Alarm flash, Super long watermark, file name setting, etc
 - Industrial plastic case and unique structure design, antidropping grade up to 2.5m
 - Interface: USB2.0
 - IP67 waterproof
 - Accessories: back clip, long shoulder clip, data cable, charger, CD, user manual



3MTA-L3

KEY FEATURES

- HD 4.0MP Body Worn Camera with Bluetooth, GPS, WIFI
- Up to 2688*1520P 30fps video resolution, support audio recording
 - One-key recording and snap shot, Up to 16 million pixels resolution for snap shot (auto/continuous)
 - 160 wide angle of view
 - Support night vision, up to 5 meters with visible face image, up to 10m with visible contour
 - Built in 4200mAh replaceable battery capacity Up to 13 hours (WIFI, BT, IR LED was closed, under 1280*720) (charging time less than 4 hours)
 - Built-in GPS: Remote Live Tracking
 - Built-in WIFI: support (2.4GHz+5GHz), for wireless video/audio transmission
 - Built-in Bluetooth: support BLE 4.1
 - Pre-record and Post-record; Multi-time period recording setting
 - Support encrypt recording video function
 - Built-in 32GB TF card standard (64GB, 128GB optional), recycle cover storage
 - One-key Important remark and Alarm flash, Super long watermark, file name setting, etc
 - Industrial plastic case and unique structure design, antidropping grade up to 2m
 - IP65 waterproof
 - Accessories: back clip, shoulder clip, base, data cable, charger, CD, user manual



4MAC-BL6

HD Body Worn Camera

KEY FEATURES

- HD4.0MP 4G Body Worn Camera with WIFI,GPS
- H.264,Up to 2688x1512P 30fps video resolution, support audio recording
- 2 inch TFT-LED high-resolution color display and playback
- One-key recording and snap shot,Up to 33 million pixels resolution for snap shot(auto/continuous)
- 170 wide angle of view,horizontal angle 140
- Support night vision, up to 6 meters with visible face image,up to 12m with visible contour
- Built in 1950mAh(2pcs detachable) replaceable battery capacity Up to 7hours(charging time less than 4 hours)
- Support 3G/4G-LTE Live Streaming
- Built-in GPS: Remote Live Tracking
- Built-in WIFI: 802.11b/g,2.4GHz,AP hotspot,or wireless video/audio transmission
- Built-in Bluetooth
- Pre-record and Post-record(operate by touch screen);Multi-time period recording setting
- Laser positioning, fixed-point and position shooting to make sure the pic will not migrate
- Support encrypt recording video function
- Built-in 32GB TF card standard(64GB,128GB optional),recycle covery storage
- Support CMS
- One-key Important remark,one-key for urgent alarm,Super long watermark,file name setting,etc
- Industrial plastic case and unique structure design,antidropping grade up to 2.5m
- Interface:Mini USB,SIM,14 PIN Multi-function port
- IP67 waterproof
- Accessories:back clip,shoulder clip,base,data cable,charger,CD,user manual



4MAB-BL4

KEY FEATURES

- HD 3.0MP Body Worn Camera
- H.264,Up to 2304x1296P 30fps video resolution, support audio recording
- 2 inch TFT-LED high-resolution color display and playback
- One-key recording and snap shot,Up to 36 million pixels resolution for snap shot(auto/continuous)
- 170 wide angle of view;16X digital Zoom
- Support night vision, up to 6 meters with visible face image,up to 12m with visible contour, White leds support lighting function at night
- Built in 1950mAh(2pcs detachable) replaceable battery capacity Up to 12hours for 2pcs battery(charging time less than 4 hours)
- Pre-record and Post-record(2-128 times);Multi-time period recording setting
- Laser positioning, fixed-point and position shooting to make sure the pic will not migrate
- Support encrypt recording video function
- Built-in 32GB TF card standard(64GB,128GB optional),recycle covery storage
- One-key Important remark and alarm flash,Super long watermark,file name setting,etc
- Industrial plastic case and unique structure design,antidropping grade up to 2.5m
- Interface:14Pin multi-function port,HDMI,USB
- IP67 waterproof
- Accessories:back clip,long shoulder clip,spare battery,base,data cable,charger,CD,user manual



3MAA-BL5

KEY FEATURES

- HD 2.0MP 4G Body Worn Camera with WIFI,GPS
- H.264,Up to1080P 30fps video resolution, support audio recording
- 2 inch TFT-LED high-resolution color display and playback
- One-key recording and snap shot,Up to 36 million pixels resolution for snap shot(auto/continuous)
- 170 wide angle of view,horizontal angle 140
- Support night vision, up to 8 meters with visible face image,up to 15m with visible contour
- Built in 1950mAh(2pcs detachable) replaceable battery capacity Up to 6hours for each battery(charging time less than 4 hours)
- Support 3G/4G-LTE Live Streaming
- Built-in GPS: Remote Live Tracking
- Built-in WIFI: 802.11b/g,2.4GHz,AP hotspot,or wireless video/audio transmission
- Built-in Bluetooth
- Built-in microphone and speaker,support two-way audio(device to device,device to CMS)
- Pre-record and Post-record;Multi-time period recording setting
- Support encrypt recording video function
- Built-in 32GB TF card standard(64GB,128GB optional),recycle covery storage
- One-key Important remark,Super long watermark,file name setting,etc
- One-key for urgent SOS alarm(send to CMS realtime recording display),support Pre-alarm message sening to CMS
- Support local video/image/audio upload to CMS and playback,can accepting the pic and text info from CMS
- Industrial plastic case and unique structure design,antidropping grade up to 2.5m
- IP67 waterproof
- Accessories:back clip,shoulder clip,base,data cable,charger,CD,user manual



2MKB-BL4



Body Worn Camera SERIES



4MAB-BL9

HD Body Worn Camera

KEY FEATURES

- HD4.0MP Body Worn Camera with WIFI,GPS,Flash Light
- Up to 2560x1440@30FPS 30fps video resolution, support audio recording;
- 2 inch TFT-LED high-resolution color display and playback
- One-key recording and snap shot,Up to 40 million pixels resolution for snap shot(auto/continuous)
- 170 wide angle of view,120 horizontal angle,this lens comes with extreme distortion self-repair ability.
- Support night vision;up to 10 meters with visible face image,up to 20m with visible contour,
- Built in 4000mAh battery replaceable capacity Up to 12 hours(charging time less than 4 hours),support one-key power-save.
- Built-in GPS: Remote Live Tracking
- Built-in WIFI: For wireless video/audio transmission(connect to mobile APP);
- Pre-record and Post-record;Multi-time period recording setting;
- Laser positioning, fixed-point and position shooting to make sure the pic will not migrate
- Support external cameras and two way talk device;Support remote control for recording,snapshot,on and off function;
- Support encrypt recording video function
- Built-in 32GB TF card standard(64GB,128GB optional),recycle cover storage
- One-key Important remark and Urgent Alarm to system,Super long watermark,file name setting,etc.
- Industrial plastic case and unique structure design,antidropping grade up to 2m
- Interface:Mini USB,14PIN multi-function port;
- IP68 waterproof
- Accessories:back clip,shoulder clip,base,data cable,charger,CD,user manual



4MAD-BL7

KEY FEATURES

- HD 2.0MP 4G Smart Headlight Camera with GPS,WIFI
- H.264,Up to 1080P@25fps video resolution, support audio recording;
- Up to 16 million pixels resolution for snap shot
- 140 wide angle of view
- Support night vision,built-in 2pcs industrial LEDs,support high beam(20m) and low beam(5m) switching;
- Built in 6000mAh replaceable battery(detachable) capacity Up to 8 hours(charging time less than 4 hours)
- Support 3G/4G-LTE Live Streaming;
- Built-in GPS: Remote Live Tracking
- Built-in WIFI: 802.11b/g,2.4GHz,for wireless video/audio transmission,AP hotspot;
- Pre-record and Post-record;Multi-time period recording setting;
- Support single-way,two way,group talking,external earphone interface
- Support encrypt recording video function
- Built-in 32GB TF card standard(64GB,128GB optional),recycle cover storage
- One-key Important remark,Super long watermark,file name setting,etc.
- One-key for urgent SOS alarm(send to CMS realtime recording display),support Pre-alarm message sending to CMS;
- Industrial plastic case and unique structure design,antidropping grade up to 2.5m
- Interface:Mini USB 2.0/3.5mm microphone port;
- IP65 waterproof



2MKE-BL8

Docking Station

KEY FEATURES

- Docking Station(Data Collection)
- Support 10 ports for data collection,4 USB port(2 USB3.0+2 USB2.0)
- 15.6"1920*1080P LED Touch Screen
- Support 1 HDD(max 8T)
- Industrial Chipset,DDR3 4G,M-SATA 60G
- Support system auto-recovery function

DCSH1-S10



KEY FEATURES

- Docking Station(Data Collection)
- Support 21 ports for data collection,transmission speed up to 14M/s
- 19"1920*1080P LED Touch Screen
- Industrial Chipset,8G memory,M-SATA 60G
- Built-in 4T HDD,can max support 8HDD(max 64T)
- Support timing Auto-On and Off setting
- Support system auto-recovery function
- UPS power supply

DCSH8-S21



ALARM SERIES

Smart WIFI Alarm

- WIFI GAS ALARM
- Operating voltage: AC 110-240V
- Warm-up Time: 180S
- Alarm Level: 7%LEL
- Sound Level: \geq 85dB/m
- Networking: WIFI
- Size: 123*78*40mm



- WIFI SMOKE ALARM
- Battery specification: CR 123A
- Sound level: 85dB/M
- Detecting area: 20 square meter
- Networking: WIFI
- SIZE: \varnothing 86*50mm



- WIFI CO&smoke alarm
- Electrochemical carbon monoxide sensor
- 2 in one sensor
- Operating Voltage: 9V Battery
- Networking: WIFI
- Alarm Sound: \leq 85dB(3m)
- Dimension: 140X41mm



AL-G01A-S

AL-S01A-BS

AL-C01A-BS

Smoke Detector

- 4wire Network Smoke Detector
- Operating voltage: DC9-35V
- Alarm output: relay output
- Dimension: 104mm dia.*51mm deep

AL-S02R4-J1

- 2wire Network Smoke Detector
- Operating voltage: DC9-35V
- Standby current: 55uA
- Alarm current: 60mA
- Alarm output: RemoteLED
- Dimension: 104mm dia.*51mm deep

AL-S02L2-J

- 4wire Network Smoke Detector
- Operating voltage: DC40-60V
- Alarm output: relay output
- Dimension: 104mm dia.*51mm deep

AL-S02R4-J2



AL-S03R4-J

- 4wire Network Smoke Detector
- Test button
- Operating voltage: DC9-35V
- Alarm output: relay output
- Dimension: 100mm dia.*42mm deep

AL-S03L2-J

- 2wire Network Smoke Detector
- Operating voltage: DC9-35V
- Standby current: 45uA
- Alarm current: 40mA
- Alarm output: RemoteLED
- Dimension: 100mm dia.*42mm deep

AL-S04R4-J

- 4wire Network Smoke Detector
- Test button
- Operating voltage: DC9-35V
- Alarm output: relay output
- Dimension: 100mm dia.*42mm deep

AL-S04L2-J



Stand Alone Smoke Detector

- Stand Alone Smoke Detector
- Wired Smoke Detector
- AC110-240V/3V lithium battery
- Alarm voice prompt
- Emergency lighting
- Unit Size: \varnothing 109*68mm



AL-S06LA-B2L

- Stand Alone Smoke Detector
- Operating voltage: 9V battery
- Alarm mode: sound & flash
- Sound level: 85dB
- Size: 107*35mm

AL-S05FA-BL

- Wireless Smoke Detector
- Operating voltage: 9V battery
- Alarm output: wireless/sound & flash alarm
- Emission frequency: 315M/433M
- Transmitting distance: 100m without block
- Encoding method: 2262/1527/trundle code
- Sound level: 85dB
- Size: \varnothing 107*35mm

AL-S05FA-BW



- Stand Alone Smoke Detector
- Operating voltage: 9V battery
- Alarm mode: sound & flash alarm
- Sound level: 85dB
- Size: 108*50mm



AL-S07FA-BL

- Stand Alone Smoke Detector
- Test button
- Operating voltage: DC9V battery
- Alarm output: 85dB
- Dimension: 100mm dia.*42mm deep
- Dimension: \varnothing 115*47mm

AL-S08A-BL

- Wired Smoke Detector
- Test button
- Operating voltage: DC9-35V
- Alarm output: relay output
- Dimension: 100mm dia.*42mm deep
- 4 Wire
- Dimension: \varnothing 115*47mm

AL-S08R4-W



- Stand Alone Smoke Detector
- Operating voltage: 9V battery
- Alarm mode: sound & flash alarm
- Sound level: 85dB
- Size: 105*69mm



AL-S09FA-BL

- Stand Alone Smoke Detector
- Operating voltage: 9V battery
- Alarm mode: sound & flash alarm
- Sound level: 85dB
- Size: 107mm dia.*44mm deep

AL-S10FA-BL

- Wireless Smoke Detector
- Operating voltage: 9V battery
- Alarm mode: wireless/sound & flash alarm
- Emission frequency: 315M/433M
- Transmitting distance: 100m without block
- Encoding method: 2262/1527/trundle code
- Sound level: 85dB
- Size: 107mm dia.*44mm deep

AL-S10FA-BW



- Stand Alone Smoke Detector
- Operating voltage: 9V battery
- Alarm mode: sound & flash alarm
- Sound level: 85dB
- Size: 140mm dia.*41mm deep

AL-S12FA-BL

- Wireless Smoke Detector
- Operating voltage: 9V battery
- Alarm mode: sound & flash alarm
- Emission frequency: 315M/433M
- Transmitting distance: 100m without block
- Encoding method: 2262/1527/trundle code
- Sound level: 85dB
- Size: 140mm dia.*41mm deep

AL-S12FA-BW

- Stand Alone Smoke Detector
- Operating voltage: AC110/220V with DC9V backup battery
- Alarm mode: sound & flash alarm
- Sound level: 85dB
- Size: 140mm dia.*41mm deep

AL-S12FA-B2L









ALARM SERIES

Stand Alone Smoke Detector

<ul style="list-style-type: none"> · Stand Alone Smoke Detector · Operating voltage: 9V battery · Alarm mode: sound & flash alarm · Sound level:85dB · Size: 140mm dia.*41mm deep 	<ul style="list-style-type: none"> · Wireless Smoke Detector · Operating voltage: 9V battery · Alarm mode: sound & flash alarm · Emission frequency:315M/433M · Transmitting distance:100m without block · Encoding method: 2262/1527/trundle code · Sound level:85dB · Size: 140mm dia.*41mm deep 	<ul style="list-style-type: none"> · Stand Alone Smoke Detector · Operating voltage: AC110/220V with DC9V backup battery · Alarm mode: sound & flash alarm · Sound level:85dB · Size: 140mm dia.*41mm deep 	
AL-S13FA-BL	AL-S13FA-BW	AL-S13FA-B2L	
			
<ul style="list-style-type: none"> · Stand Alone Smoke Detector · Operating voltage: 9V battery · Alarm mode: sound & flash alarm · Sound level:85dB · Size: 107mm dia.*35mm deep 	<ul style="list-style-type: none"> · Wireless Smoke Detector · Operating voltage: 9V battery · Alarm mode:wireless /sound & flash alarm · Emission frequency:315M/433M · Transmitting distance:100m without block · Encoding method: 2262/1527/trundle code · Sound level:85dB · Size: 107mm dia.*35mm deep 	<ul style="list-style-type: none"> · Stand Alone Smoke &Heat Detector · Operating voltage: 9V Battery · Alarm temperature: 57 C (135°F) · Sound level:85dB · Dimension:106 mm(Dia)*35mm(H) 	<ul style="list-style-type: none"> · Wireless Smoke &Heat Detector · Sound level:85dB · Alarm temperature: 57 C (135°F) · Emission frequency:315M/433M · Transmitting distance:100m without block · Encoding method: 2262/1527/trundle code · Dimension: 106 mm(Dia)*35mm(H)
AL-S11FA-BL	AL-S11FA-BW	AL-SH14A-BL	AL-SH14A-BW
			
<ul style="list-style-type: none"> · Standalone Smoke Detector · DC 9V (power by battery) · Alarm mode: sound & flash · Size: 108*32mm 	<ul style="list-style-type: none"> · Wireless Smoke Detector · DC 9V (power by battery) · Alarm mode: sound & flash · Emission frequency:315M/433M · Transmitting distance:100m without block · Encoding method: 2262/1527/trundle code · Size: 108*32mm 	<ul style="list-style-type: none"> · Standalone Smoke Detector · DC 9V (power by battery) · Alarm mode: sound & flash · Size: 108*32mm 	<ul style="list-style-type: none"> · Wireless Smoke Detector · DC 9V (power by battery) · Alarm mode: sound & flash · Emission frequency:315M/433M · Transmitting distance:100m without block · Encoding method: 2262/1527/trundle code · Size: 108*32mm
AL-S15FA-BL	AL-S15FA-BW	AL-S16FA-BL	AL-S16FA-BW

PIR Detector

<ul style="list-style-type: none"> · Wired Wide Angle PIR Detector · Alarm output: N.C./N.O. Optional · Operating voltage:DC9-16V · Detecting angle:110° · Dimension:89*52.5*38.5mm 		<ul style="list-style-type: none"> · Wired wide angle PIR detector · Alarm output N.C./N.O. Optional · Operating Voltage:DC9-16V · Detecting angle:360° · Dimension::106*36mm 	<ul style="list-style-type: none"> · Wireless wide angle PIR detector · Operating Voltage:DC9-16V · Detecting angle:360° · Alarm output:315/433 · Dimension:106*36mm 	
AL-P01N2-J		AL-P02N2-JY	AL-P02-JYW	
				
AL-P03N2-JY	AL-P04N2-J	AL-P05-BJW	AL-P06-BJW	
<ul style="list-style-type: none"> · Wired wide angle PIR detector · Alarm output N.C./N.O. Optional · Operating Voltage:DC9-16V · Detecting angle:360° · Dimension:Ø80X25mm 	<ul style="list-style-type: none"> · Wired Curtain PIR Detector · Operating voltage: DC 9-16V · Detecting angle: 15 degrees · Alarm output: N.C./ N.O. optional · Dimension: 110*69.5*40mm 	<ul style="list-style-type: none"> · Wireless Wide Angle PIR Detector · Operating voltage: 9V battery · Detecting angle: 110 degrees · Transmitting freq.: 315MHz or 433MHz · Transmitting distance: minimum 200m (in the open area) · Dimension: 107*59*45mm 	<ul style="list-style-type: none"> · Wireless Curtain PIR Detector · Operating voltage: DC 9V battery · Detecting angle: 15 degrees · Transmitting freq.: 315MHz or 433MHz · Transmitting distance: minimum 200m (in the open area) · Dimension: 110*69.5*40mm 	