

80BAI40M5A2-BR-FC-4G

4MP SenTrust HD Face Recognition Network Camera



Model Number	80BAI40M5A2-BR-FC-4G
System	
Image Sensor	1/1.8" CMOS High Performance Sensor
Min. Illumination	Color: 0.0001Lux @F1.0, B/W: 0.0001Lux@F1.0
Lens	
Lens Type	3.6-11mm motorized Lens
Lens Resolution	8MP
Illuminator	
Light Distance	IR Light 80m
IR LEDs	Infrared mode (Full color optional, need to request when placing order)
Day & Night Mode	Default Infrared Mode
Video	
Max. Image Resolution	4MP(2688x1520)@30fps
Video Compression	H.265+/H.265/H.264
Frame Rate	Main Stream: 30fps:2688x1520,2560x1440,1920x1080 Secondary Stream: 30fps:704x576,640x480 Sub-Stream: 30fps:704x576,640x480

Video Bit Rate	512Kbps~32Mbps
Character&Watermark Overlay	Support
AIISP	Support AIISP Image Enhancement
Gain Control	Support
BLC	Support
HLC	Support
Defog	Support
WDR	Digital WDR, 120 dB
Noise Reduction	3D NR/2D NR
Anti-flicker	Support
Lens Correction	Support
Mirror	Support
Electronic Shutter	1/12s-1/100000s
Audio	
Audio Input	Support, built-in microphones
Audio Output	Supports external amplifier
Audio Compression	G.711U / G.711A / G.726
Network	
Network Connection Mode	Wired
Networking Protocol	CGI,HTTP,HTTPS,GB28181,SIP,RTMP,TCP/IP,UDP,RTP,FTP,RTCP,RTSP,NTP,DHCP, DNS,DDNS,SNMP,SSL/TLS,Websocket etc.
ONVIF	Support
Web Access	With plugin preview: IE10, IE11 Plugin-free preview: Edge, Chrome, Firefox, etc.
Simultaneous Preview Number of Channels	12
Face Capture and Recognition	
Face Capture Mode	Supports multiple face capture modes with overexposure filtering.
Face Capture Recognition Priority Mode	Face Capture Recognition Priority Mode with real-time name overlay from the face database on the main stream OSD.
Face Management	Support white list, black list, VIP list management
Face Capture Scenes Configuration	Backlight environment, normal environment
Face-Recognition Records/Databases	Support up to 32 face detection per frame,100000 face records,and 50000 face databases
Face Recognition Algorithm	Built-in intelligent deep learning face algorithm, extracts target features by itself, and forms deep face images for learning
SDK	Provided SDK development kit, support secondary development, support CGI,HTTP,WEBSOCK protocol integration

Interface	
Ethernet Interface	1 RJ45 10M/100M self-adaptive Ethernet port
On-Board Storage	No
Alarm	YES
Audio	YES, Supports external amplifier
RS-485	YES
Reset	No
Antenna	2PCS
General	
POE	NO
Power Supply	DC12V±10%
Power Consumption	<10W
Surge Protection	6KV
Housing	Metal Bullet
Weather Proof	IP66
Working Temperature	-20 °C to 60 °C
Working Humidity	10%-90% (Non-condensing)

Overall Dimension Drawing

