

AH6108L2JJ201-W

8CH 2.0MP Wifi NVR KIT



Model	AH6108L2JJ201-W
System	
Operating System	Embedded LINUX operating system
Preview	1/4/9 screen
Video & Audio	
Encoding Format	H.265+/H.265/H.264
Video Input	8CH 1080P wireless Network Cameras
Audio Compression	G.711A
Audio Input	NO
Record & Playback	
Record Mode	Manual>Alarm>Motion detection>Timing
Video Resolution	1080P
Local Playback	4CH synchronous playback
Search Mode	Search by time, calendar, event, channel

Motion Detection	Support, motion detection alarm push to APP
Storage & backup	
Video Storage	HDD, Network
Backup Mode	Network, USB hard disk
Network	
Network Protocol	UPnP, DHCP, SMTP, PPPOE
APP	Supports iPhone, iPad, Android Smart phone
PC	support
External Interface	
HDMI Output	1CH, HDMI (MAX1080P)
VGA Output	1CH (MAX1080P)
Audio I/O	0/0
Alarm I/O	0/0
Network Interface	1CH RJ45 10M/100M self-adaption
WIFI antenna	2*antenna (2.4G)
USB	1* USB ports
HDD	1*SATA ports (Max 6TB/per)
General	
Power Supply	DC12V 2A
Power Consumption	NVR motherboard functions≤5W (Without HDD)
Working Temperature	-10°C- - +55°C
Working Humidity	Humidity:10%-90%, Atm:86kpa-106kpa
Camera	Metal Bullet*8 PCS
Image Sensor	1/2.7" color CMOS
Min. Illumination	Color: 0.1Lux @F1.2, B/W: 0.01Lux with IR on
Lens	3.6mm
Shutter Time	Auto
IR Distance	25m
IR Board	4 pcs IR LEDS
White Balance	Auto/indoor/outdoor
AGC	Auto
WDR	Digital WDR
DNR	3D DNR

BLC	Auto
Privacy shelter	support
Motion detecting	support
Video & Audio	
Max. Image Resolution	1080P (1920*1080)
Frame Rate	First bit stream:1920*1080@15FPS Second sub bit stream:640*480/352*288@15FPS
Video Compression	Support H.265+/H265/H264 Baseline
Video Bit Rate	32-5000kbps adjustable, Default 2048kbps
Image Settings	Image set, Image rollovers, Image style, OSD name
Audio Compression	G.711
Audio Bit Rate	8Kbps
Network	
Network Interface	1xRJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, DHCP, HTTP, DNS, DDNS, PPPOE, NTP
WIFI	802.11bgn
ONVIF	No
General	
Reset	Reset on OSD menu
Power Supply	DC 12V1A
Power Consumption	Max 4.5W
Weather Proof	IP66
Language Support	ENG
Working Temperature	-20 °C to 60 °C
Working Humidity	10%-95% RH (Non-condensing)
Package	
8CH WiFi NVR *1PC (with Mouse,12V 2A Power Adaptor)	
2.0MP IR Metal Bullet WiFi Camera * 8PCS	
12V 1A Power Adaptor * 8PCS	