

LME8108P1AQ2EA506

8CH 5.0MP 5 IN 1 XVR KIT



Model	LME8108P1AQ2EA506
5 IN 1 XVR	
Operating System	Embedded LINUX
Video	
Encoding Format	H.265
Monitor Quality	VGA, HDMI
Preview Ability	8*5M-N
Encode Ability	8*5M-N (5 in 1)
Decode Ability	8*5M-N (5 in 1)
Multi-mode Input	Analog: 8*5M-N; 8*4M-N; 4*1080P; Hybrid: 8*1080N(analog)+8*1080P(network); Network: 16*1080P;8*5M
Motion Detection	Each screen can be set to 192 (16 * 12) detection areas; Multi-level sensitivity can be set (Limited local channel)

Audio		
Audio Compression	G.711A	
Intercom	Support	
Record & Playback		
Record Mode	Manual>Alarm>Motion detection>Timing	
Local Playback	8CH (analog input mode)	
Search Mode	Search by time, calendar, event, channel	
Storage & backup		
Video Storage	HDD, Network	
Backup Mode	Network, USB hard disk, USB burner, SATA burner	
External Interface		
Video Input	8CH BNC	
Video Output	1CH VGA, 1ch HDMI	
Audio I/O	4/1	
Network Interface	RJ45 10M/100M self-adaption	
PTZ Control	Support kinds of PTZ protocols	
USB	2* USB ports	
HDD	1*SATA ports (Max 8TB/per)	
General		
Power Supply	12V/2A	
Power Consumption	<15W (without HDD)	
Working Environment	Temperature:0°C—+55°C, Humidity:10%—90%, Atm:86kpa—106kpa	
Camera	Plastic Dome*4PCS	Plastic Bullet*4PCS
Image Sensor	1/2.7" CMOS Image Sensor	
Resolution	5MP	
Effective Pixels	2560(H) × 1920(V)	
Resolution	AHD	
Video Standard	PAL/NTSC	
Synchronization	Inter-Sync	
IR Distance	20-25m	25-30m
Lens	3.6mm/5.0MP	
Day & Night mode	External control	
Min. Illumination	0.01Lux/F1.2	

UTC	Support	
OSD	Support	
WDR	Digital WDR	
S/N Ratio	≥55dB	
Electronic Shutter	AUTO 1/50(60)~1/50000s	
White Balance	Auto	
AGC	Auto	
Video Output	AHD	
Dynamic Range	68db	
DNR	3D DNR	
Type	Indoor Plastic Dome Camera	Indoor Plastic Bullet Camera
Video Port	BNC	
Power Supply	12 V DC±10%	
Lightning protection	Support	
Power Consumption	Max 5W	
Working Humidity	Relative humidity less than 90%	
Operating Temp	-20°C to +50°C (- 14°F to 122°F)	
Storage Temp.	-40°C to +60°C (-40°F to 140°F)	
Package		
8CH 5 IN 1 XVR (Mouse,12V 2A Power Adaptor) *1PC		
5.0MP IR Plastic Bullet Camera * 4PCS		
5.0MP IR Plastic Dome Camera * 4PCS		
15M BNC & Power Cable * 8PCS		
1 Split to 4 Power Line * 2PCS		
12V 2A Power Adaptor for Camera * 2PCS		