

# MP-B501H3-I200-HPA2

33X Zoom 5" Smart AI Alert POE Network PTZ Dome Camera



<b>Model Number</b>	<b>MP-B501H3-I200-HPA2</b>
<b>PTZ</b>	
Pan	Pan: 0-360 degrees continuous rotation; speed 180°/s
Tilt	Tilt:(-5) - (90°); speed 100°/s
Preset	255PCS
Line Scan	1 x AB line scan
Patrol	4
Auto Scan	1
Park Action	Preset/patrol/Auto-scan/A-B scan/patrol tracking
IR LEDs	6pcs high quality dot matrix infrared LEDs + 4pcs long-range laser infrared LEDs
IR Distance	120M
IR LEDs Control	Automatic/near light/middle light/far light/off
<b>Video</b>	
Image Sensor	1/3" color CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0.005Lux (IR Lights turn on)
S/N	≥48dB (AGC off)
Video Compression	H265/H264

Resolution	2.0MP 1920 (H) X 1080(V)
Video Bit Rate	1024Kbps-4Mbps support self-adjustable as needed
Video Resolution	Main stream: 1920x1080@25fps Sub-stream: 640x480@25fps
Audio Coding	G.711u / 64Kbps
Audio Input	Built in microphone for voice monitoring
Audio Output	Built in speaker, support voice broadcast and intercom
<b>Lens</b>	
Lens	33X Optical Zoom
Focal Length	4.5-148.5mm
Pan View Angle	60.1 ° - 2.28 ° (wide angle - defocus)
Aperture	F1.4-F4.2
<b>Function</b>	
AGC	High/Mid-High/Mid/ Mid-Low/Low
WDR	Digital WDR
DNR	3D DNR
BLC	Auto
Exposure	Program mode/shutter mode (1/5-1/100000s) / support slow shutter
Number of Visitor	Main stream: three users; Sub-stream: three users
Network Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP,RTSP,P2P
Compatibility	Seamless working with HIKIVISION platforms. Support ONVIF 2.6;
Mobile Remote Control	Support Android & iOS system mobile to access
<b>Smart</b>	
Humanoid Detection & Alert	Support, alert area can be customized
Humanoid Tracking	Support single preset point alert and multiple preset point patrol alert (up to 5 preset points for cruise tracking)
Voice Broadcast	Support human shape detection linkage sound alarm
Automatic Mode	Support power on action, rotation speed can be adjusted automatically according to lens multiple size
<b>Interface</b>	
Video Interface	RJ45 network interface
Power Supply	DC 12V/4A, POE
<b>General</b>	
POE Standard	IEEE802.3at
Working Temperature	-20 °C to 60 °C
Working Humidity	<90% (no frostless)
Power Consumption	Max 24W
Housing	Metal PTZ Dome

Protection	TVS4000V lightning protection, surge protection, voltage transient protection
Weather Proof	IP66
Product Size	F 258(mm)x242(mm)

**USA Office Contact:**

MAPESEN INTERNATIONAL INC.  
Email: [info@mapesen.com](mailto:info@mapesen.com)  
Direct Line: +1 (562) 2399826  
Main office: 6676N. BAIN AVE  
PRESNO CA 93722

**P.R.C Contact:**

Email: [info@mapesen.com](mailto:info@mapesen.com)  
TEL: +86 755 89345865  
Direct Line: 0086 755 89345865  
Main Office:  
B2-2, Zone B, Twelve Oaks  
Manor, South Bulong Rd, Longgang  
District, Shenzhen, China

