

MP-F1B5I216R-WT

Smart Wifi Standalone SD I TF Card Vandalproof Dome Camera



Model Number	MP-F1B5I216R-WT
Camera	
Image Sensor	1/2.7" SONY color CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0.005Lux with IR on
Lens	3.6mm
Shutter Time	Auto
IR Distance	25-30m
IR Board	15pcs IR LEDs
White Balance	Auto
AGC	Auto
WDR	Real WDR
DNR	2D/3D DNR
BLC	Auto
HLC	Auto
Video	
Max. Image Resolution	1080P(1920x1080)
Frame Rate	Main code stream:1080P/720P@25fps(50HZ)/30fps(60HZ) Auxiliary stream:704*576/640x352
Video Compression	Support H265,H.264 Main Profile & H.264 Baseline

Video Bit Rate	32Kbps-6144Kbps support self-adjustable as needed, default 2048Kbps
Image Settings	Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable
Bit Superposition	Support OSD name, time and date information superposition
Web Access	Support IE, Google, Firefox Browser
Audio	
Audio I/O	No
Network	
Network Interface	1* RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP, SMTP, FTP, DHCP, DNS DDNS, NTP, UPNP, RTSP
WIFI	WiFi 802.11b/g/n
ONVIF	ONVIF2.4
AP Hotspot	Support
System	
Alarm I/O	Motion detection alarm, Human detection
Storage	Max support 128GB SD card, timing video storage, motion detection video storage
Motion Detection	4 windows motion detection areas can be set (sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox, the pic and video be upload to FTP Server
General	
Working Temperature	-10 °C to 60 °C
Working Humidity	10%-95% (Non-condensing)
Reset	Support
Power Supply	DC12V±10%
Power Consumption	Max 4.5W
Housing	Vandalproof Dome
Weather Proof	IP66
Language Support	CHN/ENG