

# MP-F1B5I302-WT

Smart Wifi Standalone SD I TF Card Vandalproof Dome Camera



<b>Model Number</b>	MP-F1B5I302-WT
<b>Camera</b>	
Image Sensor	1/2.7" color CMOS,Hisilicon
Min. Illumination	Color: 0.1Lux @F1.2, B/W: 0.01Lux with IR on
Lens	3.6mm
Shutter Time	Auto
IR Distance	20-25m
IR Board	15pcs IR leds
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	3D DNR
BLC	Auto
HLC	Auto
<b>Video</b>	
Max. Image Resolution	3MP(2304x1296)@20fps

Frame Rate	Main code stream:3MP(2304x1296)@20fps Auxiliary stream:800x448@20fps
Video Compression	H.265/H.264
Video Bit Rate	32Kbps-6144bps support self-adjustable as needed,default 1024Kbps
Image Settings	Brightness,Contrast,Saturation,Exposure,Upside Down,Mirror Adjustable
Bit Superposition	Support OSD name,time and date information superposition
Web Access	Support IE,Google,Firefox Browser
<b>Audio</b>	
Audio I/O	No
<b>Network</b>	
Network Interface	1*RJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, HTTP, TCP, ICMP,UDP,ARP,ICMP,SMTP,FTP,DHCP,DNS DDNS,NTP,UPNP,RTSP
WIFI	WiFi 802.11b/g/n
ONVIF	ONVIF2.4
AP Hotspot	Support
<b>System</b>	
Alarm I/O	Motion detection alarm
Storage	Max support 64GB SD card,timing video storage,motion detection video storage;
Motion Detection	4 windows motion detection areas can be setting(sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox,the pic and video be upload to FTP Server
<b>General</b>	
Working Temperature	-10 °C to 60 °C
Working Humidity	10%-95% (Non-condensing)
Power Supply	DC12V±10%
Power Consumption	Max 4W
Housing	Vandalproof Dome
Weather Proof	IP66
Language Support	CHN(S)/CHN(T)/ENG/KOR/JPN