

# MP-L1KI206-G1TA2, MP-L1KI206-G2TA2

## Smart 4G Wifi Bullet Camera



|                    |   |
|--------------------|---|
| Model (Euro)       | MP-L1KI206-G1TA   |
| Model (America)    | MP-L1KI206-G2TA   |
| <b>Camera</b>      |   |
| Image Sensor       | 1/2.7" color CMOS   |
| Effective Pixels   | 1920(H)×1080(V)   |
| Frame Rate         | Main code stream:1080P/720P@15fps<br>Auxiliary stream:640x352/320*176 |
| Code Format        | H.264   |
| Code Rate          | 32Kbps~6144Kbps adjustable  |
| Day & Night Mode   | Color/B&W/EXTERN  |
| Min. Illumination  | Color: 0.1Lux @F1.2, B/W: 0.01Lux with IR on                          |
| IR board           | 36pcs IR leds   |
| Infrared Distance  | 30-35m  |
| Electronic Shutter | Auto  |
| White Balance      | Auto  |
| AGC                | Auto  |
| WDR                | Digital WDR   |

|                        |  |
|------------------------|--|
| DNR                    | 3D DNR   |
| <b>Lens</b>            |  |
| Focal Length           | 3.6mm  |
| Lens Type              | 2 Megapixel Fixed Lens   |
| <b>Functions</b>       |  |
| Motion Detection       | Support  |
| Email Alert            | Support  |
| Alarm linkage          | The mobile detection alarm is pushed to the APP  |
| Mirror Image           | Flip horizontal/vertical   |
| Audio                  | Voice intercom, built-in microphone and speaker  |
| Storage                | Built-in Micro SD card slot, Max 64G, timer capture  |
| Web Access             | Support IE, Google, Firefox browser  |
| Language               | ENG / CHN  |
| <b>Network</b>         |  |
| Network Interface      | 1*RJ45 10M/100M Ethernet Port  |
| Networking Protocol    | TCP/IP, HTTP, TCP, UDP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP                                    |
| WIFI                   | WiFi 802.11b/g/n   |
| AP                     | Support  |
| ONVIF                  | N/A  |
| P2P                    | Support Max 6users,browsing at the same time (each stream: 3 users )                                   |
| Mobile Surveillance    | iOS, Android   |
| PC                     | Support  |
| 4G Europe Standard(G1) | 4G FDD-LTE: B1/B3/B7/B8/B20; 4G TDD-LTE: B38/B40/B41;<br>3G WCDMA: B1/B8; 2G GSM/EDGE: 1800MHZ/900MHZ; |
| 4G USA Standard(G2)    | 4G FDD-LTE: B1/B2/B4/B5/B12/B13/B17/B25/B26;<br>3G WCDMA: B1/B8; 2G GSM/EDGE: 1800MHZ/900MHZ;          |
| <b>General</b>         |  |
| Working Temperature    | -20 °C to +50 °C (- 14 °F to 122 °F )  |
| Working Humidity       | 10%-90% RH (Non-condensing)  |
| Power Supply           | DC12V±10%/POE 48V(Optional)  |
| Lightning protection   | GB/T17626.5,IEC61000-4-5   |
| Power Consumption      | Max 5W   |
| Housing                | Outdoor Metal Bullet   |
| Weather Proof          | IP67   |