

# MP-L2JQ301F-P

3.0MP Realtime POE Network Metal Bullet Camera



|                       |   |
|-----------------------|---|
| <b>Model Number</b>   | <b>MP-L2JQ301F-P</b>  |
| <b>Camera</b>         |   |
| Image Sensor          | 1/2.9" color SONY CMOS  |
| Min. Illumination     | Color: 0.01Lux @F1.2, B/W: 0Lux with IR on  |
| Lens                  | 3.6mm   |
| Shutter Time          | Auto  |
| IR Distance           | 30-35m  |
| IR Board              | 4pcs IR array LEDS  |
| White Balance         | Auto / Manual   |
| AGC                   | Auto  |
| WDR                   | Digital WDR   |
| DNR                   | 2D/3D DNR   |
| BLC                   | support   |
| HLC                   | support   |
| <b>Video</b>          |   |
| Max. Image Resolution | 3MP (2304*1296) @25fps,1080P(1920x1080) @30fps  |
| Frame Rate            | Main code stream:3MP@25fps;1080P/720P/D1@30fps;<br>Auxiliary stream: D1/VGA/640x352/CIF@30fps |
| Video Compression     | H265+/H265/H264   |

|                      |   |
|----------------------|---|
| Video Bit Rate       | 500Kbps-4096Kbps support self-adjustable as needed                              |
| Image Settings       | Brightness, Contrast, Saturation, Exposure, Upside Down, Mirror Adjustable      |
| Bit Superposition    | Support OSD name, time and date information superposition                       |
| Web Access           | Internet explorer 6.0 and above (Web Server embedded in device) browser         |
| <b>Audio</b>         |   |
| Audio I/O            | No  |
| Audio compression    | G.711   |
| <b>Network</b>       |   |
| Network Interface    | 1*RJ45 10M/100M Ethernet Port   |
| Networking Protocol  | TCP/IP, HTTP, RTSP, DHCP, NTP, UPNP   |
| ONVIF                | ONVIF2.6  |
| APP                  | Support android, IOS  |
| PC                   | Support   |
| <b>System</b>        |   |
| Alarm I/O            | Motion detection alarm  |
| Storage              | No  |
| Motion Detection     | 22*18 windows motion detection areas can be setting (sensitivity setting 1-100) |
| Video Mask           | Support   |
| Action with Alarm    | Push to mobile APP  |
| <b>General</b>       |   |
| Language Support     | CHN(S)/CHN(T)/ENG   |
| POE                  | IEEE802.3af   |
| Power Supply         | DC12V±10% / POE   |
| Power Consumption    | Max 4W  |
| Lightning protection | 2KV   |
| Housing              | Metal Bullet  |
| Weather Proof        | IP67  |
| Working Temperature  | -30 °C to 85 °C   |
| Working Humidity     | 10%-95% (Non-condensing)  |