

MP-L2QSH400LF-A

4.0MP Full Color with Auto-adjusted Light 4-IN-1 Metal Bullet Camera



Model number	MP-L2QSH400LF-A
Camera	
Image Sensor	1/3"Color CMOS Image Sensor
Resolution	4MP@15/25/30fps
Effective Pixels	2560(H)×1440(V)
Resolution	AHD/HDCVI/HDTVI:4.0Mega Pixel,4MP,CVBS:1000TVL
Video Standard	PAL/NTSC(UTCswitch)
Synchronization	Inter-Sync
Feature	
Light Distance	30-35m
Lamp plate	6pcs Auto-adjust Light
Day & Night mode	Full Color Day&Night
UTC	Yes
OSD Support	Support
WDR	Digital WDR
Min. Illumination	0.001Lux/F1.2
S/N Ratio	≥45dB
Electronic Shutter	Auto
White Balance	Auto / Manual
AGC	Auto

Video Output	AHD/TVI/CVI/CVBS Switch by OSD menu
Dynamic Range	65db
DNR	2D/3D DNR
Language	ENGLISH/CHN
Lens	
Focal Length	3.6mm special starlight lens
Lens Mount	M12
Lens Type	Fixed
Angle of View	Horizontal: 78° Vertical: 55°
General	
Type	Outdoor Metal Bullet Camera
Power Supply	12V DC±10%
Lightning Protection	6KV
Power Consumption	4.5W
Working Humidity	Relative humidity less than 90%
Operating Temperature	-20°C to +50°C (-14°F to 122°F)
Storage Temperature	-40°C to +60°C (-40°F to 140°F)