

## MP-L2QSI301LF

## 3.0MP Full Color with Auto-adjusted Light Network Metal Bullet Camera





| Model No.             | MP-L2QSI301LF   |  |
|-----------------------|---|--|
| Camera                |   |  |
| Image Sensor          | 1/2.9" color CMOS   |  |
| Day & night Mode      | FULL COLOR DAY&NIGHT  |  |
| Lens                  | 3.6mm   |  |
| Shutter Time          | Auto  |  |
| Light Distance        | 30-35m  |  |
| Lamp Plate            | 6pcs Auto-adjust LEDS   |  |
| White Balance         | Auto / Manual   |  |
| AGC                   | Auto  |  |
| WDR                   | Digital WDR   |  |
| DNR                   | 2D/3D DNR   |  |
| BLC                   | support   |  |
| HLC                   | support   |  |
| Video                 |   |  |
| Max. Image Resolution | 3MP(2304*1296)@25fps,1080P(1920x1080)@30fps                           |  |
| Frame Rate            | Main code stream:3MP@25fps;1080P/720P/D1@30fps;                       |  |
|                       | Auxiliary stream: D1/VGA/640x352/CIF@30fps                            |  |
| Video Compression     | H265+/H265/H264   |  |
| Video Bit Rate        | 500Kbps-4096Kbps support self-adjustable as needed                    |  |
| Image Settings        | Brightness,Contrast,Saturation,Exposure,Upside Down,Mirror Adjustable |  |

## IP – Colorful Day&Night Series | MP-L2QSI301LF



| Bit Superposition    | Support OSD name, time and date information superposition                       |  |
|----------------------|---|--|
| Web Access           | Internet explorer 6.0 and above (Web Server embedded in device) browser         |  |
| Audio                |   |  |
| Audio I/O            | No  |  |
| Audio compression    | G.711   |  |
| Network              |   |  |
| Network Interface    | 1*RJ45 10M/100M Ethernet Port   |  |
| Networking Protocol  | TCP/IP, HTTP, RTSP, DHCP, NTP, UPNP   |  |
| ONVIF                | ONVIF2.6  |  |
| APP                  | Support android, IOS  |  |
| PC                   | Support   |  |
| System               |   |  |
| Alarm I/O            | Motion detection alarm  |  |
| Storage              | No  |  |
| Motion Detection     | 22*18 windows motion detection areas can be setting (sensitivity setting 1-100) |  |
| Video Mask           | Support   |  |
| Action with Alarm    | Push to mobile APP  |  |
| General              |   |  |
| Language Support     | CHN(S)/CHN(T)/ENG   |  |
| POE                  | No  |  |
| Power Supply         | DC12V±10%   |  |
| Power Consumption    | Max 4W  |  |
| Lightning protection | Support   |  |
| Housing              | Metal bullet  |  |
| Weather Proof        | IP67  |  |
| Working Temperature  | -30 °C to 85 °C   |  |
| Working Humidity     | 10%-95% (Non-condensing)  |  |