

MP-NVR616128HE

128CH 16HDD Network Digital Video Recorder



Model	MP-NVR616128HE
System	
Operating System	Embedded LINUX
Video & Audio Input	
Bidirectional Talk	1CH, RCA (Line in,2Vp-p,1Kohms)
Incoming bandwidth	384Mbps
IPC Input	128CH
Video & Audio Output	
VGA	1CH,1920×1080,1280×1024,1280×720,1024×768
HDMI	Standard 1.4b, 3840×2160,1920×1080,1280×1024,1280×720,1024×768
Audio Output	1CH, RCA (Line out,2Vp-p,300ohms)
Video & Audio Encoding	
Audio Compression	G.711A
Audio Bit Rate	64Kbps
Video & Audio Decoding	
IP channel Resolution	Main stream: up to 3264x2448 Auxiliary stream: D1 max

Video decoding	MPEG-4 / H.264 Up to High Profile@Level5.0)
Audio decoding	G.711A, G.726
Synchronous Playback	Up to 16CH
Decoding Ability	16CH 1080P@30FPS
Other Function	
Bidirectional Talk	Two-way voice intercom function
Motion Detection	Zones: 396(22*18), Sensitivity: 1~6 (level 6 is the highest)
Picture Capture	Support JPEG Capture
Intelligent Analysis	N/A
Interface	
Network Interface	2 RJ45 10M/100M/1000 self-adaptive Ethernet interface
USB Interface	3 USB2.0 Interfaces
Serial Interface	1 RS-232 interface, 1 RS-485 interface
Audio Input / Output	1CH, RCA (Line out,2Vp-p,300ohms)
Alarm Input	16CH, Open/Closed Relay
Alarm Output	4CH, NO/NC
Storage	
SATA	16*SATA HDD Interface, 1 e SATA Interface
Capacity	Unlimited
Network	
Network Protocols	IPV4, TCP, UDP, RTSP, HTTP, DNS, DDNS, DHCP, NTP, SMTP, UPNP
Format	
Video Compression	H.265+ /H.265(HEVC) /H.264+ /H.264
General	
Compatibility	ONVIF
Dimensions	600x560x260mm
Size	3U,600*560*260mm
Weight	15KG (without HDD)
Installation	Rack installation, Desktop installation
Power Supply	110V~220V±10%, 47Hz~63Hz
Consumption	30W (without HDD)
Working Conditions	Temperature: 0°C--+55°C Humidity: 10%~90%