

MP-NVR6208HS-P8

8CH 2 HDD **POE(8 Ports)** Network Digital Video



Model	MP-NVR6208HS-P8
System	
Operating System	Embedded LINUX
Video & Audio Input	
Bidirectional Talk	1CH, RCA (Line in,2Vp-p,1Kohms)
Incoming bandwidth	64Mbps
IPC Input	8CH
Video & Audio Output	
VGA	1CH,1920×1080,1280×1024,1280×720,1024×768
HDMI	Standard 1.4b, 3840x2160,1920×1080,1280×1024,1280×720,1024×768
Audio Output	1CH, RCA (Line out,2Vp-p,300ohms)
Video & Audio Encoding	
Audio Compression	G.711A
Audio Bit Rate	8Kbps(16bit)
Video & Audio Decoding	
IP channel Resolution	Main stream: up to 3264x2448 Auxiliary stream: D1

Video decoding	H.265 (Main Profile@L5.0 High-tie) /H.264 (Up to High Profile@Level5.1)
Audio decoding	G.711A/G.711U/G.726
Synchronous Playback	Up to 8CH
Decoding Ability	8CH 720P@30FPS or 4CH 1080P@30FPS
Other Function	
Bidirectional Talk	Two-way voice intercom function
Motion Detection	Zones: 396(22*18), Sensitivity: 1~6 (level 6 is the highest)
Picture Capture	Support JPEG Capture
Intelligent Analysis	1CH Face detection or 1CH Perimeter detection, Up to 1080P
Interface	
POE Interface	8CH, IEEE 802.3af, RJ-45 10/100 Mbps self-adaptive Ethernet interface
POE Power	≤90W
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet interface
USB Interface	1 USB2.0 Interfaces,2 USB3.0 Interfaces
Serial Interface	1 RS-485 Interface
Audio Input / Output	1CH, RCA (Line out,2Vp-p,300ohms)
Alarm Input	8CH, Open/Closed Relay
Alarm Output	4CH, NO/NC
Storage	
SATA	2*SATA HDD
Capacity	Unlimited
Network	
Network Protocols	IPV4, TCP, UDP, RTSP, HTTP, DNS, DDNS, DHCP, NTP, SMTP, UPNP
Format	
Video Compression	H.265+ /H.265(HEVC)/H.264+ /H.264
General	
Compatibility	ONVIF
Dimensions	405*335*120mm
Size	360*262*48mm
Weight	2.3KG (without HDD)
Installation	Desktop Installation
Power Supply	DC 48V 1.875A(POE)
Consumption	6W(without HDD)
Working Conditions	Temperature: -10°C- +55°C Humidity: 10%~90%

