

NVR204PL2JE200

4CH H.265 2.0MP POE NVR KIT



Model	NVR204PL2JE200
4CH POE NVR	
Operating System	Embedded LINUX
Preview	1/4/9 screen
Video & Audio	
Encoding Format	H.265+ / H.265 / H.264
Video Input	9CH 1080P IP Network Cameras
Audio Compression	G.711A
Audio Input	IPC composite stream network audio input
Smart Analysis	
With Smart IPC Support	Target Count, Object Left/Lost, Area Detection, Line Crossing
Record & Playback	
Record Mode	Manual>Alarm>Motion detection>Timing
Video Resolution	1080P
Local Playback	Support adaptive stream preview and playback: 9 screens D1, 4 screens 1280*720, single screen 1920*1080

Search Mode	Search by time, calendar, event, channel
Storage & backup	
Video Storage	HDD, Network
Backup Mode	Network, USB hard disk, USB burner, SATA burner
Network	
Network Protocol	UPnP (Plug & Play), SNMP (Simple Network Management), NTP (Network Timekeeping), SADP (Device Network Search), SMTP (Mail Service), NFS (Access NAS), iSCSI (IP SAN Application), PPPOE (Dial-up Internet access), DHCP (automatically obtain IP address)
POE standard	IEEE802.3af
APP	Supports iPhone, iPad, Android Smart phone
PC	support
External Interface	
HDMI Output	1CH, HDMI can output audio at the same time
VGA Output	1CH
Audio I/O	0/0
Alarm I/O	0/0
Network Interface	RJ45 10M/100M self-adaption
POE interface	4xRJ45 10M/100M adaptive Ethernet port
PTZ Control	Support kinds of PTZ protocols
USB	2* USB ports
HDD	1*SATA ports (Max 8TB/per)
General	
Power Supply	52V 1.5A
Power Consumption	POE power consumption≤40W; NVR motherboard function≤8W (without HDD)
Working Environment	-10°C- +55°C
Working Humidity	10%—90%, Atm:86kpa—106kpa
Camera	Metal Bullet*4PCS
Image Sensor	1/2.9" CMOS Image Sensor
Resolution	1080P and below resolution
Max. Image Resolution	1920(H) × 1080(V)
Frame Rate	First bit stream:1920*1080@20FPS Second sub bit stream:704*576,640*480
Video Compression	Support H.265 main profile&H.264 baseline

Video Bit Rate	16Kbps-6Mbps continuously adjustable, support CBR / VBR
Image Settings	Support for brightness, contrast, saturation, white balance, AWB (automatic white balance), AGC (automatic gain), AE (automatic exposure); support privacy area; normal / 90 ° / 270 ° image rotation; Automatic, manual color to black and other switches.
Audio Compression	G.711
Audio Bit Rate	64Kbps
IR Distance	30-35m
Lens	3.6mm/2.0MP
Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0Lux with IR on
WDR	Digital WDR
Electronic Shutter	AUTO 1/50(60)~1/50000s
White Balance	Auto
AGC	Auto
BLC	Auto
DNR	3D DNR
Smart Analysis	Target Count, Object Left /Lost, Area Detection, Line Crossing
Network Interface	1xRJ45 10M/100M Ethernet Port
Networking Protocol	TCP/IP, DHCP, HTTP, HTTPS NTP, DNS, RTP RTSP
ONVIF	Support
POE	Support
Type	Outdoor Metal Bullet Camera
Weather Proof	IP67
Power Supply	DC 12V
Lightning protection	Support
Power Consumption	Max 4W
Working Humidity	10%-95% RH(Non-condensing)
Working Temperature	-10°C to +60°C
Package	
4CH POE NVR *1PC	
2.0MP IR Metal Bullet POE IP Camera * 4PCS	
52V 1.5A Power Adaptor * 1PC	
15M Network Cable * 4PCS	