

# VR-T1C5I500-WTA2

5.0MP 360° Panaramic Wifi SD I TF Card Bullet Camera



<b>Model number</b>	VR-T1C5I500-WTA2
<b>Camera</b>	
Image Sensor	1/2.8" CMOS Image Sensor
Min. Illumination	Color: 0.01Lux @F1.2, B/W:0.005Lux with IR on
WDR	ON/OFF
Lens	360 Degree lens
Shutter Time	default
IR Distance	adjustable
BLC	Default
HLC	Default
<b>Video</b>	
Max Image Resolution	5MP
Frame Rate	Main stream: 2560*1920@20fps
Video Compression	Support H265, H.264 Main Profile & H.264 Baseline
Video Bit Rate	32Kbps-6144Kbps support self-adjustable, default 1536Kbps
Image Settings	Brightness, Contrast, Saturation, Exposure Adjustable

Bit Superposition	Support OSD name
<b>Audio</b>	
Audio I/O	Two-way audio, built-in microphone and speaker
Audio Compression	G.711
<b>Network</b>	
Communication	1*RJ45 10M/100M Ethernet Port
Network Protocols	TCP/IP, HTTP, ICMP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP
Wifi	Wifi 802.11b/g/n
ONVIF	ONVIF2.4
AP Hotspot	Support
<b>System</b>	
Alarm I/O	Motion detection Alarm
Storage	Max support 128G SD card, timing video storage, motion detection video storage
Motion Detection	4 windows motion detection areas can be setting (sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox, the picture and video be upload to FTP server
APP	Support android,IOS
<b>General</b>	
Working Temperature	-10°C-60°C
Working Humidity	10-95%(Non-condensing)
Power Supply	DC 12V±10%(Optional)
Power Consumption	5W
Working Humidity	Relative humidity less than 90%
Language Support	CHN(S)/ENG
Cover Color	White