

VR-T1G5I500-WTA2

5.0MP 360° Panaramic Wifi SD I TF Card Camera





























(III)	Wiſ
	Wil
HD	Wi I

Model number	VR-T1G5I500-WTA2	
Camera		
Image Sensor	1/2.8" CMOS Image Sensor	
Min. Illumination	Color: 0.01Lux @F1.2, B/W:0.005Lux with IR on	
WDR	ON/OFF	
Lens	360 Degree lens	
Shutter Time	default	
IR Distance	adjustable	
BLC	Default	
HLC	Default	
Video		
Max Image Resolution	5MP	
Frame Rate	Main stream: 2560*1920@20fps	
Video Compression	Support H265, H.264 Main Profile & H.264 Baseline	
Video Bit Rate	32Kbps-6144Kbps support self-adjustable, default 1536Kbps	
Image Settings	Brightness, Contrast, Saturation, Exposure Adjustable	
Bit Superposition	Support OSD name	
Audio		
Audio I/O	Two-way audio, built-in microphone and speaker	
Audio Compression	G.711	

Smart Wifi Panaramic Series | VR-T1G5I500-WTA2



Network		
Communication	1*RJ45 10M/100M Ethernet Port	
Network Protocols	TCP/IP, HTTP, ICMP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP	
Wifi	Wifi 802.11b/g/n	
ONVIF	ONVIF2.4	
AP Hotspot	Support	
System		
Alarm I/O	Motion detection Alarm	
Storage	Max support 128G SD card, timing video storage, motion detection video storage	
Motion Detection	4 windows motion detection areas can be setting (sensitivity setting 1-100)	
Video Mask	4 windows can be built to mask your private area	
Action with Alarm	The alarm pictures be sent to appoint mailbox, the picture and video be upload to	
	FTP server	
APP	Support android,IOS	
General		
Working Temperature	-10°C-60°C	
Working Humidity	10-95%(Non-condensing)	
Power Supply	DC 12V±10%(Optional)	
Power Consumption	5W	
Working Humidity	Relative humidity less than 90%	
Language Support	CHN(S)/ENG	
Cover Color	White	