

VR-T1H5I500-WTA2

360 Panaromic Wifi SD I TF Card Bullet Camera



Model number	VR-T1H4I500-WTA2
Camera	
Image Sensor	1/2.8" SONY CMOS
Min. Illumination	Color: 0.01Lux @F1.2, B/W:0.005Lux with IR on
WDR	Digital WDR
Lens	360 Degree lens
Shutter Time	default
IR Distance	25-35M
BLC	Default
HLC	Default
Video	
Max Image Resolution	5MP
Frame Rate	Main stream: 2560*1920@15fps
Video Compression	Support H265, H.264 Main Profile & H.264 Baseline
Video Bit Rate	32Kbps-6144Kbps support self-adjustable, default 2048Kbps
Image Settings	Brightness, Contrast, Saturation, Exposure Adjustable
Bit Superposition	Support OSD name
Audio	
Audio I/O	Two-way audio, built-in microphone and speaker
Audio Compression	G.711

Network	
Communication	1*RJ45 10M/100M Ethernet Port
Network Protocols	TCP/IP, HTTP, ICMP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP
WiFi	WiFi 802.11b/g/n
ONVIF	ONVIF2.4
AP Hotspot	Support
System	
Alarm I/O	Motion detection Alarm
Storage	Max support 128G SD card, timing video storage, motion detection video storage
Motion Detection	4 windows motion detection areas can be set (sensitivity setting 1-100)
Video Mask	4 windows can be built to mask your private area
Action with Alarm	The alarm pictures be sent to appoint mailbox, the picture and video be upload to FTP server
APP	Support android, IOS
General	
Working Temperature	-10°C-60°C
Working Humidity	10-95%(Non-condensing)
Reset	Support
Power Supply	DC 12V±10%(Optional)
Power Consumption	5W
Working Humidity	Relative humidity less than 90%
Language Support	CHN(S)/ENG