

# YH6104L2KI500-W

4CH H.265 5.0MP Wireless Security Camera System (Support Tuya APP)



<b>Model</b>	YH6104L2KI500-W
<b>System</b>	
Operating System	Embedded LINUX operating system
Preview	1/4 screen
<b>Video &amp; Audio</b>	
Encoding Format	H.265/H.264
Video Input	4CH 5MP wireless Network Cameras
Audio Compression	G.711A
Audio Input	NO
<b>Smart</b>	
Human detection	Support
Motion Detection	Support, motion detection alarm push to APP
<b>Record &amp; Playback</b>	

Record Mode	Manual>Alarm>Motion detection>Timing
Video Resolution	Max 5MP
Local Playback	4CH synchronous playback
Search Mode	Search by time, calendar, event, channel
<b>Storage &amp; backup</b>	
Video Storage	HDD, Network
Cloud Storage	Support
Backup Mode	Network, USB hard disk
<b>Network</b>	
Network Protocol	TCP/IP,HTTP,NTP,DHCP,UDP,ARP,DDNS,DNS,P2P
APP	Android/IOS (TUYA)
PC	No
<b>Smart</b>	
Human detection	Support AI human detection
Motion Detection	Support, motion detection alarm push to APP
Automatic cascade	Support
<b>External Interface</b>	
HDMI Output	1CH, HDMI (MAX1080P)
VGA Output	1CH (MAX1080P)
Audio I/O	0/0
Alarm I/O	0/0
Network Interface	1CH RJ45 10M/100M self-adaption
WIFI antenna	2 pcs 5db antenna (2.4G)
USB	2* USB ports
HDD	1*SATA ports (Max 6TB/per)
<b>General</b>	
Power Supply	DC12V 2A
Power Consumption	NVR motherboard functions≤5W (Without HDD)
Language	English (Support for multiple languages)
Working Temperature	-20°C - +60°C
Working Humidity	Humidity:10%-90%, Atm:86kpa-106kpa
<b>Camera</b>	
Image Sensor	1/2.8" 5.0MP progressive scan CMOS

Min. Illumination	Color: 0.01Lux @F1.2, B/W: 0.001Lux with IR on
Lens	3.6mm
Shutter Time	Auto
IR Distance	30-35m
IR Board	2 pcs IR ARRAY LEDS
White Balance	Auto
AGC	Auto
WDR	Digital WDR
DNR	3D DNR
BLC	Auto
AI intelligent	Human detection
Motion detecting	Support
<b>Video &amp; Audio</b>	
Max. Image Resolution	5MP (2592*1944)
Frame Rate	First bit stream:2592*1944@15FPS Second sub bit stream:640*480/352*288@15FPS
Video Compression	Support H.265/H264 Baseline
Video Bit Rate	Auto
Image Settings	Image set, Image style, OSD name
<b>Network</b>	
Networking Protocol	TCP/IP, DHCP, HTTP, DNS,NTP
WIFI standard	IEEE802.11++
WIFI frequency	2.4G
ONVIF	No
<b>General</b>	
Power Supply	DC 12V1A
Power Consumption	Max 4W
Network Interface	No
Weather Proof	IP67
Working Temperature	-20 °C to 60 °C
Working Humidity	10%-95% RH (Non-condensing)
<b>Package</b>	
4CH WiFi NVR *1PC (with Mouse,12V 2A Power Adaptor)	
5.0MP IR Metal Bullet WiFi Camera * 4PCS	

HD WIFI NVR KIT Series | YH6104L2KI500-W

**mapesen**<sup>®</sup>

12V 1A Power Adaptor \* 4PCS

1M Network Cable \* 1PC